

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1088218S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 06/10/2017 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Wednesday, 20 May 2020

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary				
Project name	Sean Krajsic			
Street address	221 Caddens Road	Caddens 2747		
Local Government Area	Penrith City Council			
Plan type and plan number	deposited 1229230			
Lot no.	220			
Section no.	-			
Project type	separate dwelling house			
No. of bedrooms	2			
Project score				
Water	✓ 43	Target 40		
Thermal Comfort	✓ Pass	Target Pass		
Energy	У 54	Target 50		

Certificate Prepared by

Name / Company Name: Peace Plan Designers

ABN (if applicable): 13952041743

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1088218S Wednesday, 20 May 2020 page 1/9

Document Set ID: 9162057 Version: 1. Version Date: 02/06/2020

Description of project

Project address	
Project name	Sean Krajsic
Street address	221 Caddens Road Caddens 2747
Local Government Area	Penrith City Council
Plan type and plan number	Deposited Plan 1229230
Lot no.	220
Section no.	-
Project type	
Project type	separate dwelling house
No. of bedrooms	2
Site details	
Site area (m²)	600
Roof area (m²)	311
Conditioned floor area (m2)	177.0
Unconditioned floor area (m2)	8.0
Total area of garden and lawn (m2)	251

Assessor details and thermal lo	ads	
Assessor number	n/a	
Certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m².year)	n/a	
Area adjusted heating load (MJ/m².year)	n/a	
Project score		
Water	. 4	
	43	Target 40
Thermal Comfort	✓ 43 ✓ Pass	Target 40 Target Pass

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1088218S Wednesday, 20 May 2020 page 2/9

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 3 star (> 7.5 but <= 9 L/min) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 3 star in each toilet in the development.		V	V
The applicant must install taps with a minimum rating of 3 star in the kitchen in the development.		V	
The applicant must install basin taps with a minimum rating of 3 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 4000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	V
The applicant must configure the rainwater tank to collect rain runoff from at least 311 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	V
The applicant must connect the rainwater tank to:			
all toilets in the development		✓	V
the cold water tap that supplies each clothes washer in the development		~	V
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		~	V

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1088218S Wednesday, 20 May 2020 page 3/9

Document Set ID: 9162057 Version: 1, Version Date: 02/06/2020

Thermal Comfort Commitments		Show on CC/CDC plans & specs	Certifier check
General features			
The dwelling must not have more than 2 storeys.	V	✓	V
The conditioned floor area of the dwelling must not exceed 300 square metres.	V	V	V
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	V	V
The dwelling must not contain third level habitable attic room.	V	~	V
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	V	V	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - brick veneer	2.06 (or 2.60 including construction)	
internal wall shared with garage - plasterboard	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 2.95 (up), roof: foil backed blanket (55 mm)	unventilated; dark (solar absorptance > 0.70)

Note	Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.
Note	• In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1088218S Wednesday, 20 May 2020 page 4/9

Document Set ID: 9162057 Version: 1, Version Date: 02/06/2020

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights	·		
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	-	✓	~
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	V	~	V
The following requirements must also be satisfied in relation to each window and glazed door:	V	~	V
• For the following glass and frame types, the certifier check can be performed by visual inspection.			-
- Aluminium single clear			
- Aluminium double (air) clear			
- Timber/uPVC/fibreglass single clear			
- Timber/uPVC/fibreglass double (air) clear			

Window/glazed door no.	Maximum height (mm)	Maximum width (mm)	Туре	Shading Device (Dimension within 10%)	Overshadowing
North facing					
W01	2100	2400	aluminium, single, clear	eave 600 mm, 90 mm above head of window or glazed door	not overshadowed
W02	2100	2400	aluminium, single, clear	eave 600 mm, 90 mm above head of window or glazed door	not overshadowed
East facing					
W03	2400	2400	aluminium, single, clear	verandah 3450 mm, 2400 mm above base of window or glazed door	not overshadowed
W04	1200	1000	aluminium, single, clear	eave 600 mm, 90 mm above head of window or glazed door	not overshadowed
W05	1200	3000	aluminium, single, clear	eave 600 mm, 90 mm above head of window or glazed door	not overshadowed
W06	600	1200	aluminium, single, clear	eave 600 mm, 90 mm above head of window or glazed door	not overshadowed

Certificate No.: 1088218S

Document Set ID: 9162057

BASIX

Version: 1, Version Date: 02/06/2020

Planning, Industry & Environment www.basix.nsw.gov.au

600	1200		10%)	
	1200	aluminium, single, clear	eave 600 mm, 90 mm above head of window or glazed door	not overshadowed
2100	900	aluminium, single, clear	verandah 1000 mm, 2190 mm above base of window or glazed door	not overshadowed
2100	2700	aluminium, single, clear	eave 600 mm, 90 mm above head of window or glazed door	not overshadowed
2100	900	aluminium, single, clear	eave 600 mm, 90 mm above head of window or glazed door	not overshadowed
1200	1500	aluminium, single, clear	eave 600 mm, 90 mm above head of window or glazed door	not overshadowed
1200	1500	aluminium, single, clear	eave 600 mm, 90 mm above head of window or glazed door	not overshadowed
	2100 2100 1200	2100 2700 2100 900 1200 1500	2100 2700 aluminium, single, clear 2100 900 aluminium, single, clear 1200 1500 aluminium, single, clear	base of window or glazed door 2100 2700 aluminium, single, clear eave 600 mm, 90 mm above head of window or glazed door 2100 900 aluminium, single, clear eave 600 mm, 90 mm above head of window or glazed door 1200 1500 aluminium, single, clear eave 600 mm, 90 mm above head of window or glazed door 1200 1500 aluminium, single, clear eave 600 mm, 90 mm above head of eave 600 mm, 90 mm above head of

Planning, Industry & Environment www.basix.nsw.gov.au

BASIX

Document Set ID: 9162057 Version: 1, Version Date: 02/06/2020 Certificate No.: 1088218S

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 4 stars.	-	~	-
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 2 star (average zone)		~	-
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 2 star (average zone)		V	-
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 2 star (average zone)		→	~
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: 2 star (average zone)		~	~
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: no mechanical ventilation (ie. natural); Operation control: n/a		~	-
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		✓	•
Laundry: natural ventilation only, or no laundry; Operation control: n/a		✓	V
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or light emitting diode (LED) lamps:			
at least 2 of the bedrooms / study;		_	-
at least 1 of the living / dining rooms;		V	-
• the kitchen;			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1088218S Wednesday, 20 May 2020 page 7/9

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
all bathrooms/toilets;		~	V
• the laundry;		~	V
• all hallways;		~	V
Natural lighting			
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.	~	~	V
Alternative energy			
The applicant must install a photovoltaic system with the capacity to generate at least 1 peak kilowatts of electricity as part of the development. The applicant must connect this system to the development's electrical system.	~	~	~
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.			

BASIX Planning, Industry & Environment www.basix.nsw.gov.au Version: 3.0 / DARWINIA_3_11_6 Certificate No.: 1088218S Wednesday, 20 May 2020 page 8/9

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

BASIX

Document Set ID: 9162057 Version: 1. Version Date: 02/06/2020 Certificate No.: 1088218S