BASIX Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 491157S


This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 29/06/2009 published by the Department of Planning. This document is available at www.basix.nsw.gov.au

Director-General

Date of issue: Tuesday, 02 July 2013

To be valid, this certificate must be lodged within 3 months of the date of issue.





Project summary		
Project name	Lot 2231 Jordan Sp	orings Estate
Street address	Katandra Place Jor	dan Springs 2747
Local Government Area	Penrith City Counci	il
Plan type and plan number	deposited 1168992	
Lot no.	2231	
Section no.		
Project type	separate dwelling h	nouse
No. of bedrooms	4	
Project score		
Water	√ 40	Target 40
Thermal Comfort	✓ Pass	Target Pass
Energy	✓ 46	Target 40



Certificate Prepared by	HIGHY COUNCIL
Name / Company Name: Craig Guyer	
ABN (if applicable): 50414996141	

Description of project

Project address	
Project name	Lot 2231 Jordan Springs Estate
Street address	n/a Katandra Place Jordan Springs 2747
Local Government Area	Penrith City Council
Plan type and plan number	Deposited Plan 1168992
Lot no.	2231
Section no.	
Project type	是是是是一个人的
Project type	separate dwelling house
No. of bedrooms	4
Site details	
Site area (m²)	378
Roof area (m²)	230
Conditioned floor area (m2)	124
Unconditioned floor area (m2)	7
Total area of garden and lawn (m2)	84

Assessor number	n/a	
Certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m².year)	n/a	
Area adjusted heating load (MJ/m².year)	n/a	was to be a second
Other		17.2
none	n/a	
Project score	2 2 3 4 10	
Water	√ 40	Target 40
Thermal Cornfort	✓ Pass	Target Pass
Energy	√ 46	Target 40

Schedule of BASIX commitments

BASIX

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 3 star (> 7.5 but <= 9 L/min) in all showers in the development.		1	1
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		1	1
The applicant must install taps with a minimum rating of 4 star in the kitchen in the development.		1	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development,	ll .	1	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 5000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	1	1	1
The applicant must configure the rainwater tank to collect rain runoff from at least 47 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		1	1
The applicant must connect the rainwater tank to:			
all toilets in the development		1	1
 the cold water tap that supplies each clothes washer in the development 		1	1
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		1	1

Department of Planning www.basix.nsw.gov.au Version 6.23 / CASUARINA 2_16_2 Certificate No. 491157S Tuesday, 02 July 2013 page 3/9

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Floor, walls and ceiling/roof			and the same of
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	1	1	1

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	N-CO-DUCK - NACC
external wall - brick veneer	1.66 (or 2.20 including construction)	
internal wall shared with garage - plasterboard	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 3 (up), roof: foil/sarking	unventilated; medium (solar absorptance 0.475-0.70)

Note Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.

Version: 6 23 / CASUARINA_2_16_2 Department of Planning www basix nsw gov au

Certificate No. 491157S

Tuesday, 02 July 2013

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	1	1	1
The dwelling may have 1 skylight (<0.7 square metres) and up to 2 windows/glazed doors (<0.7 square metres) which are not listed in the table.	1	1	1
 Except where the glass is 'single clear' or 'single toned', each window and glazed door must have a U-value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) +/-10% of that listed. Total system U-values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. 	1	1	1
 The leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 millimetres above the head of the window or glazed door, except that a projection greater than 500 mm and up to 1500 mm above the head must be twice the value in the table. 	1	1	1
 Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35. 		1	1
 Unless they have adjustable shading, pergolas must have fixed battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm. 		1	1

Windowiglazed door no.	Orientation	Maximum area (square metres)	Туре	Shading	Overshadowing
Bed 2	N	1.89	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 901-1,200 mm	not overshadowed
Bed 2	N	1.89	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
Bed 4	E	2.16	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
Bath	E	1.8	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
wc	Е	0.54	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
Bed 3	E	2.16	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed

Window/glazed door no.	Orientation	Maximum area (square metres)	Туре	Shading	Overshadowing
Living	E	1.89	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
Living	S	3.78	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony >2,000 mm	not overshadowed
Living	SE	4.41	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony >2,000 mm	not overshadowed
Dining	S	1.89	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
Dining	S	1.89	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
Kitchen	W	1.89	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
Bed 1	w	4.41	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
Ens	W	0.54	improved aluminium, single clear (U-value:6.44, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 3 stars.	1	1	1
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: ceiling fans + 1-phase airconditioning; Energy rating: 1 Star (new rating)		1	1
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: ceiling fans; Energy rating: n/a		1	1
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 1 Star (new rating)		1	1
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		1	1
Ventilation			
The applicant must install the following exhaust systems in the development:	17-2	Water thank the same	1-7-7 9-N
At least 1 Bathroom: individual fan, not ducted; Operation control: manual switch on/off		1	1
Kitchen: individual fan, not ducted; Operation control: manual switch on/off			
Laundry: natural ventilation only, or no laundry; Operation control: n/a		1	1
Lauriory, natural ventilation only, or no lauriory, Operation control. Il/a		1	1
Artificial lighting			
The applicant must ensure that the "primary type of artificial lighting" is fluorescent or light emitting diode (LED) lighting in each of the following rooms, and where the word "dedicated" appears, the fittings for those lights must only be capable of accepting fluorescent or ight emitting diode (LED) lamps:			
at least 4 of the bedrooms / study;			
• the launday	-	,	1
the laundry;		1	1
all hallways;		1	1

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	1	1	1
The applicant must install a window and/or skylight in 3 bathroom(s)/toilet(s) in the development for natural lighting.	1	1	1
Other:			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		1	
The applicant must install a fixed outdoor clothes drying line as part of the development.		1	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a / in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

Certificate No. 491157S Tuesday, 02 July 2013