BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 653855S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 18/09/2014 published by Planning & Infrastructure. This document is available at www.basix.nsw.gov.au

Director-General Date of issue: Thursday, 10 September 2015 To be valid, this certificate must be lodged within 3 months of the date of issue.



Project summary				
Project name	850 Richmond Road, Berkshire Park-granny flat			
Street address	850 Richmond Road Berkshire Park 2765			
Local Government Area	Penrith City Council			
Plan type and plan number	deposited 1097876			
Lot no.	4			
Section no.	-			
Project type	separate dwelling house			
No. of bedrooms	2			
Project score				
Water	V 40 Target 40			
Thermal Comfort	V Pass Target Pass			
Energy	V 44 Target 40			

Certificate Prepared by
Name / Company Name: SIA Designarch

ABN (if applicable): 97530120507

BASIX Planning & Infrastructure

ucture www.basix.nsw.gov.au

Version: 6.37 / CASUARINA 2 33 0

Certificate No.: 653855S

Description of project

Project address

Project name	850 Richmond Road, Berkshire Park-granny flat		
Street address	850 Richmond Road Berkshire Park 2765		
Local Government Area Penrith City Council			
Plan type and plan number	Deposited Plan 1097876		
Lot no.	4		
Section no.	-		
Project type			
Project type	separate dwelling house		
No. of bedrooms 2			
Site details			
Site area (m²)	500		
Roof area (m ²)	100		
Conditioned floor area (m2)	46.0		
Unconditioned floor area (m2)	4.53		
Total area of garden and lawn (m2)	100		

Assessor details and thermal lo	ads	
Assessor number	n/a	
Certificate number	n/a	
Climate zone	n/a	
Area adjusted cooling load (MJ/m ² .year)	n/a	
Area adjusted heating load (MJ/m ² .year)	n/a	
Other		
none	n/a	
Project score		
Water	40	Target 40
Thermal Comfort	V Pass	Target Pass
Energy	V 44	Target 40

BASIX Planning & Infrastructure

cture www.basix.nsw.gov.au

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifie check
Fixtures			
The applicant must install showerheads with a minimum rating of 3 star (> 6 but <= 7.5 L/min) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 4 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 4 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 4 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 2500 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 100 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
all toilets in the development		~	~
 the cold water tap that supplies each clothes washer in the development 		 Image: A second s	~

BASIX Planning & Infrastructure

ure www.basix.nsw.gov.au

Version: 6.37 / CASUARINA_2_33_0

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - brick veneer	1.66 (or 2.20 including construction)	
internal wall shared with garage - plasterboard	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 3 (up), roof: foil/sarking	unventilated; dark (solar absorptance > 0.70)

Note Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	~	~	~
The dwelling may have 1 skylight (<0.7 square metres) and up to 2 windows/glazed doors (<0.7 square metres) which are not listed in the table.	~	~	~
The following requirements must also be satisfied in relation to each window and glazed door:	~	~	~
 Except where the glass is 'single clear' or 'single toned', each window and glazed door must have a U-value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) +/-10% of that listed. Total system U-values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. 			~
 The leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 millimetres above the head of the window or glazed door, except that a projection greater than 500 mm and up to 1500 mm above the head must be twice the value in the table. 	~	~	~
• Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.		~	~
 Unless they have adjustable shading, pergolas must have fixed battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm. 		~	~

Window/glazed door no.	Orientation	Maximum area (square metres)	Туре	Shading	Overshadowing
W17,W18	NE	7.60	improved aluminium, single pyrolytic low-e (U-value:4.48, SHGC:0.46)	eave/verandah/pergola/balcony 450 mm	not overshadowed
W16	NW	0.88	standard aluminium, single clear (or U-value:7.63, SHGC:0.75)	eave/verandah/pergola/balcony 450 mm	not overshadowed
W13,W14,W15	SW	6.51	standard aluminium, single pyrolytic low-e (U-value:5.7, SHGC:0.47)	eave/verandah/pergola/balcony 450 mm	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 4 stars.	~	~	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: EER 3.0 - 3.5		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: EER 3.0 - 3.5		~	~
The cooling system must provide for day/night zoning between living areas and bedrooms.		v	~
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: EER 3.0 - 3.5		~	~
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning; Energy rating: EER 3.0 - 3.5		v	~
The heating system must provide for day/night zoning between living areas and bedrooms.		 	~
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		 Image: A set of the set of the	~
Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off		~	~
Laundry: natural ventilation only, or no laundry; Operation control: n/a		~	~
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	~	~
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	~	~	~

BASIX Planning & Infrastructure

cture www.basix.nsw.gov.au

Version: 6.37 / CASUARINA_2_33_0

Certificate No.: 653855S

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.		~	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a v in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a v in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a v in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.