

## LANDSCAPE PLAN HAS BEEN PREPARED IN ACCORDANCE WITH THE PENRITH DEVELOPMENT CONTROL PLAN 2014.

| LANDSCAPED AREA                                   |                               |
|---|-------------------------------|
| TOTAL SITE AREA:                                  | 685.6m <sup>2</sup>           |
| TOTAL LANDSCAPE AREA:<br>(EXCLUDES HARD SURFACES) | 354.0m <sup>2</sup><br>51.63% |
| MIN. REQUIRED:                                    | 40%                           |

## MAINTENANCE PROCEDURES

- LAWN TO BE FERTILISED TWICE A YEAR IN THE WARM MONTHS, MOWING WEEKLY IN 1) SUMMER MONTHS AND FORTNIGHTLY OR MONTHLY AS REQUIRED IN THE WINTER MONTHS
- PLANTS TO BE FERTILISED A MINIMUM OF TWICE A YEAR AT THE SAME TIME OF 2) PRUNING. TO DO THIS USE A COMPLETE FERTILISER, KEEP MULCH CLEAR OF TREE TRUNK AREA. AFTER PLANT/SHURBS AND TREES ARE PLANTED CONTINUE TO WATER WELL ONCE A WEEK
- PRUNE HEDGE PLANTS A MINIMUM OF 2 3 TIMES A YEAR, IN THE WARMER MONTHS. 3) WAIT FOR AT LEAST 10MM OF NEW GROWTH BEFORE PRUNING AGAIN TO PROMOTE HEALTHY NEW GROWTH

NOTES:

RFV


Δ

- ALL LANDSCAPED AREAS TO HAVE A MINIMUM 1:100 FALL TOWARDS STORM WATER DRAINS. OR 1) AWAY FROM THE BUILDING FOR POSSIBLE OVERLAND WATER DRAINAGE.
- A TREE PROTECTION ZONE (TPZ) SHALL BE ESTABLISHED FOR THE DURATION OF ANY WORKS 2) NEAR ANY EXISTING TREES, AS PER THE METHOD OUTLINED IN THE CURRENT AS4970-2009. PERMISSION FROM THE COUNCIL ARBORIST IS REQUIRED FOR ACTIVITIES THAT DO NOT COMPLY WITH THE CURRENT AUSTRALIAN STANDARDS.
- DRIVEWAY LAYOUT TO BE CONSTRUCTED FROM ARCHITECTURAL CONSTRUCTION DRAWINGS RETAINING WALLS ALONG SIDE BOUNDARIES BETWEEN LOTS TO BE FINALISED ON SITE AFTER 4)
- BENCHING.
- 5) ALL RETAINING WALLS VISIBLE FROM THE STREET TO BE MASONRY WITH COLOURS MATCHING THOSE ON THE FRONT FACADE OF THE DWELLING.
- ALL IMPORTED SOIL TO GARDEN AREAS TO BE OF PREMIUM GARDEN MIX STANDARD AT 300MM 6) DFPTH
- TURF TO BE LAID ON A 150MM MINIMUM BASE OF 80% SAND 20% SOIL MIX. REFER TO DETAIL.
- ALL GARDEN AREAS TO BE COVERED WITH A MINIMUM OF 75MM OF 14MM PINE BARK MULCH.
- GARDEN EDGING IS TO BE INSTALLED BETWEEN ALL ADJOINING SOFT LANDSCAPE FINISHES. REFER TO DETAIL.

DATE

27.05.21

KR



**ISSUE / DESCRIPTION** 

Initial design for DA