

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 512550S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 29/06/2009 published by the Department of Planning. This document is available at www.basix.nsw.gov.au

Director-General

Date of issue: Wednesday, 30 October 2013

To be valid, this certificate must be lodged within 3 months of the date of issue.



| Project summary | | | | | |
|---------------------------|---------------------|------------------------------|--|--|--|
| Project name | 20130198_AI_LOt 2 | 20130198_AI_LOt 2308 Patanga | | | |
| Street address | na Patanga Cresce | nt Jordan Springs 2747 | | | |
| Local Government Area | Penrith City Counci | l | | | |
| Plan type and plan number | deposited na | deposited na | | | |
| Lot no. | 2308 | 2308 | | | |
| Section no. | E | - | | | |
| Project type | separate dwelling h | separate dwelling house | | | |
| No. of bedrooms | 4 | | | | |
| Project score | | | | | |
| Water | ✓ 41 | Target 40 | | | |
| Thermal Comfort | ✓ Pass | Target Pass | | | |
| Energy | √ 40 | ✓ 40 Target 40 | | | |

Certificate Prepared by

Name / Company Name: arcINOVATIONZ Pty Ltd

ABN (if applicable): 15 208 786 513

BASIX Department of Planning www.basix.nsw.gov.au Version: 6.26 / CASUARINA_2_19_4 Certificate No.: 512550S Wednesday, 30 October 2013 page 1/9

Description of project

| Project address | |
|------------------------------------|---|
| Project name | 20130198_AI_LOt 2308 Patanga |
| Street address | na Patanga Crescent Jordan Springs 2747 |
| Local Government Area | Penrith City Council |
| Plan type and plan number | Deposited Plan na |
| Lot no. | 2308 |
| Section no. | |
| Project type | |
| Project type | separate dwelling house |
| No. of bedrooms | 4 |
| Site details | |
| Site area (m²) | 405 |
| Roof area (m²) | 311 |
| Conditioned floor area (m2) | 149 |
| Unconditioned floor area (m2) | 18 |
| Total area of garden and lawn (m2) | 122 |

| Assessor details and thermal lo | ads |
|---|--------------------|
| Assessor number | n/a |
| Certificate number | n/a |
| Climate zone | n/a |
| Area adjusted cooling load (MJ/m².year) | n/a |
| Area adjusted heating load (MJ/m².year) | n/a |
| Other | |
| none | n/a |
| Project score | |
| Water | ✓ 41 Target 40 |
| Thermal Comfort | ✓ Pass Target Pass |
| Energy | ✓ 40 Target 40 |

BASIX Department of Planning www.basix.nsw.gov.au Version: 6.26 / CASUARINA_2_19_4 Certificate No.: 512550S Wednesday, 30 October 2013 page 2/9

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

| Water Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|---|------------------|------------------------------|-----------------|
| Fixtures | | | |
| The applicant must install showerheads with a minimum rating of 3 star (> 4.5 but <= 6 L/min) in all showers in the development. | | 1 | / |
| The applicant must install a toilet flushing system with a minimum rating of 3 star in each toilet in the development. | | 1 | / |
| The applicant must install taps with a minimum rating of 3 star in the kitchen in the development. | | 1 | |
| The applicant must install basin taps with a minimum rating of 3 star in each bathroom in the development. | | 1 | |
| Alternative water | | | |
| Rainwater tank | | | |
| The applicant must install a rainwater tank of at least 1500 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities. | ✓ | ✓ | ✓ |
| The applicant must configure the rainwater tank to collect rain runoff from at least 150 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam). | | ✓ | / |
| The applicant must connect the rainwater tank to: | 8 | | |
| all toilets in the development | | 1 | 1 |
| the cold water tap that supplies each clothes washer in the development | | 1 | 1 |
| at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) | | ✓ | 1 |

BASIX Department of Planning www.basix.nsw.gov.au Version: 6.26 / CASUARINA_2_19_4 Certificate No.: 512550S Wednesday, 30 October 2013 page 3/9

| Thermal Comfort Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|---|------------------|------------------------------|-----------------|
| Floor, walls and ceiling/roof | | | |
| The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below. | / | ✓ | / |

| Construction | Additional insulation required (R-Value) | Other specifications |
|---|--|---|
| floor - concrete slab on ground | nil | |
| external wall - brick veneer | 1.66 (or 2.20 including construction) | |
| internal wall shared with garage - plasterboard | nil | |
| ceiling and roof - flat ceiling / pitched roof | ceiling: 3 (up), roof: foil/sarking | unventilated; dark (solar absorptance > 0.70) |

Note Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.

BASIX Department of Planning www.basix.nsw.gov.au Version: 6.26 / CASUARINA_2_19_4 Certificate No.: 512550S Wednesday, 30 October 2013 page 4/9

| Thermal Comfort Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|--|---------------------|------------------------------|-----------------|
| Windows, glazed doors and skylights | | | |
| The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door. | / | ✓ | 1 |
| The dwelling may have 1 skylight (<0.7 square metres) and up to 2 windows/glazed doors (<0.7 square metres) which are not listed in the table. | / | 1 | 1 |
| The following requirements must also be satisfied in relation to each window and glazed door: | / | 1 | / |
| Except where the glass is 'single clear' or 'single toned', each window and glazed door must have a U-value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) +/-10% of that listed. Total system U-values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. | | | 1 |
| The leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 millimetres above the head of the window or glazed door, except that a projection greater than 500 mm and up to 1500 mm above the head must be twice the value in the table. | / | 1 | 1 |
| • Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35. | | / | 1 |
| • Unless they have adjustable shading, pergolas must have fixed battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm. | | ✓ | 1 |

| Window/glazed door no. | Orientation | Maximum area (square metres) | Туре | Shading | Overshadowing |
|---------------------------------------|-------------|---------------------------------|---|--|------------------|
| W1 & W2 (Mbed & Bed 2) | W | 3.24 | standard aluminium, single clear (or U-value:7.63, SHGC:0.75) | eave/verandah/pergola/balcony 450 mm | not overshadowed |
| SD Alfresco | W | 5.67 | standard aluminium, single clear (or U-value:7.63, SHGC:0.75) | eave/verandah/pergola/balcony >2,000 mm | not overshadowed |
| W3, W4 & W5 (Family, Dining, Kitchen) | N | 3.36 | standard aluminium, single clear (or U-value:7.63, SHGC:0.75) | eave/verandah/pergola/balcony 450 mm | not overshadowed |
| SD Ldry | N | 3.15 | improved aluminium, single clear (U-value:6.44, SHGC:0.75) | eave/verandah/pergola/balcony 450 mm | not overshadowed |
| W7,W8 & W9(Living) | E | 3.24 | standard aluminium, single clear (or U-value:7.63, SHGC:0.75) | eave/verandah/pergola/balcony 450 mm | not overshadowed |
| W10 (Bed4) | S | 2.16 | standard aluminium, single clear (or U-value:7.63, SHGC:0.75) | eave/verandah/pergola/balcony 450 mm | not overshadowed |

BASIX Department of Planning www.basix.nsw.gov.au Version: 6.26 / CASUARINA_2_19_4 Certificate No.: 512550S Wednesday, 30 October 2013 page 5/9

| Window/glazed door no. | Orientation | Maximum area (square metres) | Туре | Shading | Overshadowing |
|------------------------|-------------|---------------------------------|--|---|------------------|
| W11(Bath) | S | 0.54 | standard aluminium, single clear (or U-value:7.63, SHGC:0.75) | eave/verandah/pergola/balcony 450 mm | not overshadowed |
| W12(Bed 3) | S | 2.16 | standard aluminium, single clear (or U-value:7.63, SHGC:0.75) | eave/verandah/pergola/balcony 450 mm | not overshadowed |
| W13(Media) | S | 1.08 | standard aluminium, single clear (or U-value:7.63, SHGC:0.75) | eave/verandah/pergola/balcony 450 mm | not overshadowed |
| W14(Ens) | S | 0.54 | standard aluminium, single clear (or U-value:7.63, SHGC:0.75) | eave/verandah/pergola/balcony 450 mm | not overshadowed |
| W15 & W16(M bed) | S | 2.16 | standard aluminium, single clear (or U-value:7.63, SHGC:0.75) | eave/verandah/pergola/balcony 450 mm | not overshadowed |

BASIX Department of Planning www.basix.nsw.gov.au Version: 6.26 / CASUARINA_2_19_4 Certificate No.: 512550S Wednesday, 30 October 2013 page 6/9

| lot water | DA plans | plans & specs | Certifier check |
|--|----------|---------------|-----------------|
| | | | |
| he applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 4.5 stars. | 1 | ✓ | 1 |
| Cooling system | | | |
| he applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase irconditioning; Energy rating: EER < 2.5 | | ✓ | / |
| he applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase irconditioning; Energy rating: EER < 2.5 | | 1 | 1 |
| he cooling system must provide for day/night zoning between living areas and bedrooms. | | 1 | / |
| leating system | | | |
| he applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase irconditioning; Energy rating: EER < 2.5 | | ✓ | 1 |
| he applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase irconditioning; Energy rating: EER < 2.5 | | 1 | 1 |
| he heating system must provide for day/night zoning between living areas and bedrooms. | | 1 | 1 |
| /entilation | | | |
| he applicant must install the following exhaust systems in the development: | | | T |
| At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off | | 1 | 1 |
| Kitchen: individual fan, ducted to façade or roof; Operation control: manual switch on/off | | 1 | / |
| Laundry: individual fan, ducted to façade or roof; Operation control: manual switch on/off | | 1 | 1 |
| latural lighting | | | |
| he applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting. | / | 1 | / |
| he applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting. | 1 | 1 | 1 |

BASIX Department of Planning www.basix.nsw.gov.au Version: 6.26 / CASUARINA_2_19_4 Certificate No.: 512550S Wednesday, 30 October 2013 page 7/9

| Energy Commitments | Show on DA plans | Show on CC/CDC plans & specs | Certifier check |
|--|------------------|------------------------------|-----------------|
| The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling. | | ✓ | |
| The applicant must install a fixed outdoor clothes drying line as part of the development. | | 1 | |

BASIX Department of Planning www.basix.nsw.gov.au Version: 6.26 / CASUARINA_2_19_4 Certificate No.: 512550S Wednesday, 30 October 2013 page 8/9

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a vin the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a \checkmark in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

BASIX Department of Planning www.basix.nsw.gov.au Version: 6.26 / CASUARINA 2 19 4 Certificate No.: 512550S Wednesday, 30 October 2013 page 9/9