

9m X 18m X 3.6m SHED **CONCRETE SLAB LAYOUT PLAN**

SITE

SCALE - 1:100

Version: 1, Version Date: 04/03/2016



(100mm minimum concrete slab included)

SOIL CLASSIFICATION (COMPACTED)	REINFORCING IN SLAB	EDGE BEAM	PIER	EDGE BE thickne inclu	ess not
	MESH REINFORCING	TRENCH MESH	Ø x DEPTH	DEPTH	WIDTH
A, S, & M	SL72	-	450 x 400	-	-
M - D	SL82	L11TM3	-	300	300
H TO H - D	SL82	L11TM3	-	400	300
E TO E - D	SL82	L11TM4	-	400	400
P (DROP EDGE BEAM OR STANDARD EDGE BEAM WITH PIERS UNDER COLUMNS 300 INTO FIRM GROUND)	SL82	L11TM4	450 Ø	400	400

Do not scale off the drawings unless otherwise stated and use figured dimensions in preference. All dimensions are to be checked & verified on site before the commencement of any work, all dimensions & levels are subject to final survey and set-out.

Registered Professional Engineer 341550



9m x 18m x 3.6m DATE ISSUED: 23.10.2015

JOSIP & MARYANN BASTAC FOR

307-321 CRANEBROOK ROAD, CRANEBROOK NSW 2749

NPER Civil & Structural

Mr Andrew Matiukevitch

Black Consultants

ABN 40 812 511 237 PO Box 13 Consulting Civil & Lauderdale TAS 7021 Structural Engineers blackcon@bigpond.net.au

Andrew Matiukevitch BE Dip Tech (Civil Eng) LGE MIE (Aust) CP Eng (NPER Civil & NPER Structural) RPEQ

CERTIFIED STEEL PORTAL FRAME SHED **DESIGN FOR "REGION A" TERRAIN** CATEGORY 2.0, 2.5 & 3.0 - IMPORTANCE LEVEL 2.

DOMESTIC & LIGHT INDUSTRIAL STEEL PORTAL FRAME SHED STRUCTURES

These structures are designed in compliance with AS4600, AS3600 and AS1170 1 to 4 as Importance Level 2 with a Live Load of 0.25kPa as "Air Leaky Structures" providing stability when openings are

The structures are clad with corrugated pre-painted finish, 0.42mm walls and 0.42mm roof over cold formed 450 to 550mPa galvanized steel C sections primary frames.

Primary framing is fastened together with 8.8 Class galvanized bolts adequately tensioned on ground prior to erection.

Secondary framing steel bracing, with purlins and girts lapped, are all tek fastened to primary steel with a minimum of two (2) teks per connection as specified in details.

ENGINEERING

The undersigning engineer has checked that the design of the structure complies with relevant current Australian Standards as stated above and the following

i.e AS4671-2001 Steel Reinforcing materials

AS3600 - Concrete structures

However, he will not be present during construction, neither will he conduct inspections nor construction supervision.

The class 10a buildings are designed for erection on pad footings or slab based on soil of classification "A", "S" or "M" with nominal bearing capacity 100kPa (i.e. organic soil is to be removed to a minimum of 100mm below natural surface).

Where (suitable) fill is required to level the site, it should be placed and compacted in layers of 150mm maximum.

Concrete pad footings and slab supply and placement is to be in compliance with AS2870-2011 Residential Slabs & Footings. AS3600-2009 Concrete Structures for A2 and B2 exposure (i.e. 25mPa strength @ 28 days strength) with recommended slump 75 to 80mm for light pneumatic tyred traffic all trafficable floors.

For sites where these conditions are considered to be inadequate, a customized foundation design for the structure can be supplied to suit a specific purpose.

GENERAL SLAB DESIGN FOR DOMESTIC & LIGHT INDUSTRIAL USES

Thickness 100mm with minimum 30mm cover. Refer to

Slab Foundation table for reinforcing specification.

Refer to Slab Foundation table for footing /

pier specification

CONSTRUCTION

Erection of the structure is to be in compliance with local and state

Occupational Health and Safety Regulations and with plans


provided.

GENERAL

The designs as portrayed on the drawings remain the intellectual property of Best Sheds Pty Ltd and are provided for building approval and construction purposes only and are only valid when blue ink signed and dated by the engineer

PAGE P.A. SCALE 1:100 PAGES IN SET 10.08.2012 BS 1020

The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of Best Sheds Pty Ltd with whom copyright resides.




Civil & Structural

BS 1020


Document Set ID: 7061723 Version: 1, Version Date: 04/03/2016

Value & Quality Direct to You

The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of Best Sheds Pty Ltd with whom copyright resides.



Version: 1, Version Date: 04/03/2016



tophat 120 roof
purlin with 100mm
minimum overlap

2 x 14g
tek screws.

C250 rafter


8 x M16
bolts

8 x M16
bolts

12g x 35mm long. refer to screw spacing diagram for frequency

4 x 14g tek
screws each side of apex bracket.







MEMBER SCHEDULE					
1	RAFTER	C25024			
2	COLUMN	C25024			
3	ENDWALL MULLION	C25024			
4	SLEEVE ANCHOR BOLTS	DYNA BOLT OR SIMILAR M16 X 110mm			
5	EAVE PURLIN	Tophat 120 x 1.0 + 64 x 0.75			
6	ROOF PURLIN	Tophat 120 x 1.0			
7	PURLIN SPACING (ROOF)	Space equally to max 1.0m centres			
8	PURLIN OVERLAP (ROOF)	Minimum 100mm overlap			
9	WALL GIRT	Tophat 120 x 1.0			
10	WALL GIRT SPACING	Space equally to max 1.2m centres			
11	WALL GIRT OVERLAP	Minimum 100mm overlap			
12	END WALL GIRT SIZE	Tophat 120 x 1.0			
13	END WALL GIRT SPACING	Space equally to max 1.4m centres			
14	END WALL GIRT LENGTH	Minimum 100mm overlap			
15	FRAME SCREWS	14-13X22 HEX C/S (SP HD 5/16" HEX DRIVE)			
16	FRAME BOLTS	PURLIN ASSEMBLY M16 X 40 Z/P			
17	CROSS BRACING STRAP AND FASTENERS	1 BAY (ROOF AND WALLS / 32mm x 1.2mm THICK)			
18	WALL COLOUR	PRE-PAINTED - AS SELECTED			
19	ROOF COLOUR	PRE-PAINTED - AS SELECTED			
20	ROLLER DOOR COLOUR	PRE-PAINTED - AS SELECTED			
21	PA DOOR COLOUR	PRE-PAINTED - AS SELECTED			
22	DOWNPIPE COLOUR	PRE-PAINTED - AS SELECTED			
23	GUTTER COLOUR	PRE-PAINTED - AS SELECTED			
24	CORNER FLASHING COLOUR	PRE-PAINTED - AS SELECTED			
25	BARGE FLASHING COLOUR	PRE-PAINTED - AS SELECTED			
26	OPENING FLASHING COLOUR	PRE-PAINTED - AS SELECTED			
27	OPEN BAY HEADER HEIGHT	N/A			
28	KNEE BRACE LENGTH	2.4m C15019 FIXED IN PORTALS EXCEPT END WALLS			
29	APEX BRACE LENGTH	3.4m C15019 FIXED IN PORTALS EXCEPT END WALLS			

CONNECTION DETAILS

SITE

SCALE AS SHOWN

Do not scale off the drawings unless otherwise stated and use figured dimensions in preference. All dimensions are to be checked & verified on site before the commencement of any work, all dimensions & levels are subject to final survey and set-out.



PROJECT 9m x 18m x 3.6m DATE ISSUED: 23.10.2015

FOR JOSIP & MARYANN BASTAC

307-321 CRANEBROOK ROAD, CRANEBROOK NSW 2749

The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of Best Sheds Pty Ltd with whom copyright resides.

Black Consultants


ABN 40 812 511 237

Consulting Civil & Lauderdale TAS 702'
Structural Engineers blackcon@bigpond.net.au

Andrew Matiukevitch BE Dip Tech (Civil Eng) LGE MIE (Aust) CP Eng (NPER Civil & NPER Structural) RPEQ

PAGE PAGE	PAGE	
3 SCALE AS SHOWN 4		
DATE DRAWN PAGES IN	I SET	
JOB NO. BS 1020 5		

Version: 1, Version Date: 04/03/2016



sheds Value & Quality Direct to You Document Set ID: 7061723

JOSIP & MARYANN BASTAC FOR

SITE

307-321 CRANEBROOK ROAD, CRANEBROOK NSW 2749

The design and detail shown on these drawings are applicable to this project only and may not be reproduced in whole or any part or be used for any other purpose without the written permission of Best Sheds Pty Ltd with whom copyright resides.

NPER red on the NPER In the area of practice of Civil & Structural

Consulting Civil & Lauderdale TAS 702 **Structural Engineers**

Indrew Mati	ukevitch BE Dip Tech (Civil Eng) LGE MIE (Aust) CP Eng (NPER
	Civil & NPER Structural) RPEQ
	Civil & NPER Structural) RPEQ

13 21 au	P.A.	PAGE _	
	AS SHOWN	5	
	DATE DRAWN 10.08.2012	PAGES IN SET	
	JOB NO. BS 1020	5	

Version: 1, Version Date: 04/03/2016