

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 545331S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 29/06/2009 published by Planning & Infrastructure. This document is available at www.basix.nsw.gov.au

Director-General

Date of issue: Wednesday, 28 May 2014

To be valid, this certificate must be lodged within 3 months of the date of issue.



Project name	Lot 2292 Tengala D Lot A	Orive, Jordan Springs.	
Street address	Binalong Street Jordan Springs 2747		
Local Government Area	Penrith City Counci	I	
Plan type and plan number	deposited 1168993		
Lot no.	2292		
Section no.	-		
Project type	separate dwelling house		
No. of bedrooms	4		
Project score			
Water	✓ 41	Target 40	
Thermal Comfort	✓ Pass	Target Pass	
Energy	✓ 47	Target 40	

Certificate Prepared by	ertificate Pre	epared l	οу
-------------------------	----------------	----------	----

Name / Company Name: JR Design & Drafting

ABN (if applicable): 66319680618

BASIX Planning & Infrastructure www.basix.nsw.gov.au Version: 6.29 / CASUARINA_2_24_8_1 Certificate No.: 545331S Wednesday, 28 May 2014 page 1/8

Description of project

Project address	
Project name	Lot 2292 Tengala Drive, Jordan Springs. Lot A
Street address	n/a Binalong Street Jordan Springs 2747
Local Government Area	Penrith City Council
Plan type and plan number	Deposited Plan 1168993
Lot no.	2292
Section no.	-
Project type	
Project type	separate dwelling house
No. of bedrooms	4
Site details	
Site area (m²)	288
Roof area (m²)	168
Conditioned floor area (m2)	111
Unconditioned floor area (m2)	10
Total area of garden and lawn (m2)	100

Assessor details and thermal lo	oads
Assessor number	n/a
Certificate number	n/a
Climate zone	n/a
Area adjusted cooling load (MJ/m².year)	n/a
Area adjusted heating load (MJ/m².year)	n/a
Other	
none	n/a
Project score	
Water	✓ 41 Target 40
Thermal Comfort	✓ Pass Target Pass
Energy	✓ 47 Target 40

BASIX Planning & Infrastructure www.basix.nsw.gov.au Version: 6.29 / CASUARINA_2_24_8_1 Certificate No.: 545331S Wednesday, 28 May 2014 page 2/8

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 3 star (> 4.5 but <= 6 L/min) in all showers in the development.		~	
The applicant must install a toilet flushing system with a minimum rating of 2 star in each toilet in the development.		V	V
The applicant must install taps with a minimum rating of 3 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 3 star in each bathroom in the development.		V	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 2000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 167.91 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	V
The applicant must connect the rainwater tank to:			
all toilets in the development		~	V
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		V	V

BASIX Planning & Infrastructure www.basix.nsw.gov.au Version: 6.29 / CASUARINA_2_24_8_1 Certificate No.: 545331S Wednesday, 28 May 2014 page 3/8

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Floor, walls and ceiling/roof			
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	V	~	~

Construction	Additional insulation required (R-Value)	Other specifications
floor - concrete slab on ground	nil	
external wall - brick veneer	1.66 (or 2.20 including construction)	
internal wall shared with garage - plasterboard	nil	
ceiling and roof - flat ceiling / pitched roof	ceiling: 3 (up), roof: foil/sarking	unventilated; medium (solar absorptance 0.475-0.70)

Note Insulation specified in this Certificate must be installed in accordance with Part 3.12.1.1 of the Building Code of Australia.

BASIX Planning & Infrastructure www.basix.nsw.gov.au Version: 6.29 / CASUARINA_2_24_8_1 Certificate No.: 545331S Wednesday, 28 May 2014 page 4/8

Thermal Comfort Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Windows, glazed doors and skylights			
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each window and glazed door.	V	~	~
The dwelling may have 1 skylight (<0.7 square metres) and up to 2 windows/glazed doors (<0.7 square metres) which are not listed in the table.	V	~	~
The following requirements must also be satisfied in relation to each window and glazed door:	V	~	V
 Except where the glass is 'single clear' or 'single toned', each window and glazed door must have a U-value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) +/-10% of that listed. Total system U-values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions. 			V
 The leading edge of each eave, pergola, verandah, balcony or awning must be no more than 500 millimetres above the head of the window or glazed door, except that a projection greater than 500 mm and up to 1500 mm above the head must be twice the value in the table. 	~	~	V
• Pergolas with polycarbonate roof or similar translucent material must have a shading coefficient of less than 0.35.		V	V
• Unless they have adjustable shading, pergolas must have fixed battens parallel to the window or glazed door above which they are situated, unless the pergola also shades a perpendicular window. The spacing between battens must not be more than 50 mm.			

Window/glazed door no.	Orientation	Maximum area (square metres)	Туре	Shading	Overshadowing
W1,W2	W	2.16	standard aluminium, single clear (or U-value:7.63, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
W3,W4,W5,W6,W7	N	8.44	standard aluminium, single clear (or U-value:7.63, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
W8	E	4.62	standard aluminium, single clear (or U-value:7.63, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
W9	E	2.16	standard aluminium, single clear (or U-value:7.63, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed
W10,W11,W12	S	4.93	standard aluminium, single clear (or U-value:7.63, SHGC:0.75)	eave/verandah/pergola/balcony 451-600 mm	not overshadowed

BASIX Planning & Infrastructure www.basix.nsw.gov.au Version: 6.29 / CASUARINA_2_24_8_1 Certificate No.: 545331S Wednesday, 28 May 2014 page 5/8

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water			
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 3 stars.	~	V	V
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 1 Star (new rating)		V	V
The bedrooms must not incorporate any cooling system, or any ducting which is designed to accommodate a cooling system.		V	V
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning; Energy rating: 1 Star (new rating)	2	~	V
The bedrooms must not incorporate any heating system, or any ducting which is designed to accommodate a heating system.		V	V
Ventilation			
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: no mechanical ventilation (ie. natural); Operation control: n/a		V	V
Kitchen: individual fan, not ducted; Operation control: manual switch on/off		V	V
Laundry: natural ventilation only, or no laundry; Operation control: n/a		V	V
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~		V
The applicant must install a window and/or skylight in 2 bathroom(s)/toilet(s) in the development for natural lighting.	~	~	V
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.			

BASIX Planning & Infrastructure www.basix.nsw.gov.au Version: 6.29 / CASUARINA_2_24_8_1 Certificate No.: 545331S Wednesday, 28 May 2014 page 6/8

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
The applicant must construct each refrigerator space in the development so that it is "well ventilated", as defined in the BASIX definitions.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.		~	

Planning & Infrastructure Wednesday, 28 May 2014 www.basix.nsw.gov.au Version: 6.29 / CASUARINA_2_24_8_1 Certificate No.: 545331S BASIX

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate(either interim or final) for the development may be issued.

BASIX Planning & Infrastructure www.basix.nsw.gov.au Version: 6.29 / CASUARINA_2_24_8_1 Certificate No.: 545331S Wednesday, 28 May 2014 page 8/8