

# PENRITH CITY COUNCIL

## NOTICE OF DETERMINATION

### DESCRIPTION OF DEVELOPMENT

Application number:	DA15/1182
Description of development:	Alterations and Additions to an Existing Facility to Incorporate a New Freezer and Transition Area
Classification of development:	Class 8

### DETAILS OF THE LAND TO BE DEVELOPED

Legal description:	Lot 12 DP 1087962
Property address:	24 - 27 Lambridge Place, PENRITH NSW 2750

### DETAILS OF THE APPLICANT

Name & Address:	Gibson Six Pty Ltd 24-27 Lambridge Place PENRITH NSW 2750
-----------------	---

### DECISION OF CONSENT AUTHORITY

In accordance with Section 81(1) (a) of the Environmental Planning and Assessment Act 1979, consent is granted subject to the conditions listed in attachment 1.

Please note that this consent will lapse on the expiry date unless the development has commenced in that time.

Date from which consent operates	19 January 2016
Date the consent expires	19 January 2018
Date of this decision	11 January 2016

## POINT OF CONTACT

---

If you have any questions regarding this determination you should contact:

Assessing Officer:	Hannah Gilvear
Contact telephone number:	+612 4732 7714

## NOTES

---

### **Reasons**

The conditions in the attached schedule have been imposed in accordance with Section 80A of the Environmental Planning and Assessment Act 1979 as amended.

### **Conditions**

Your attention is drawn to the attached conditions of consent in attachment 1.

### **Certification and advisory notes**

You should also check if this type of development requires a construction certificate in addition to this development consent

It is recommended that you read any Advisory Note enclosed with this notice of determination.

### **Review of determination**

The applicant may request Council to review its determination pursuant to Section 82A of the Environmental Planning and Assessment Act 1979 within 6 months of receiving this Notice of Determination.

You cannot make this request if the development is Designated Development, Integrated Development or State Significant development or if the application was decided by a Joint Regional Planning Panel.

### **Appeals in the Land and Environment Court**

The applicant can appeal against this decision in the Land and Environment Court within six (6) months of receiving this Notice of Determination.

You cannot appeal if a Commission of Inquiry was held for the subject development application, or if the development is a State Significant Development.

An appeal to the Land and Environment Court is made by lodging an application to the Court in accordance with the Rules of the Court.

### **Designated development**

If the application was for designated development and a written objection was made in respect to the application, the objector can appeal against this decision to the Land and Environment Court within 28 days after the date of this notice. The objector cannot appeal if a Commission of Inquiry was held.

If the applicant appeals against this decision, objector(s) will be given a notice of the appeal and the objector(s) can apply to the Land and Environment Court within 28 days after the date of this appeal notice to attend the appeal and make submissions at that appeal.

### **Joint Regional Planning Panels**

If the application was decided by a Joint Regional Planning Panel, please refer to Section 23H of the Environmental Planning and Assessment Act, 1979 (as amended) for any further regulations.

## ATTACHMENT 1: CONDITIONS OF CONSENT

### General

- 1 The development must be implemented substantially in accordance with the plans stamped approved by Council, and any supporting information received with the application, except as may be amended in red on the attached plans and by the following conditions.

Drawing Title	Plan No.	Issue	Prepared By	Date
Floor Plan	CP201510_FB1	A	Alex Krnjulac	06-10-2015
Elevations and Section	CP201510_FB2	A	Alex Krnjulac	6-10-2015
Stormwater Drainage	CP201510_FB3	A	Alex Krnjulac	06-10-2015
Existing Site Plan	CP201512_FB4	A	Alex Krnjulac	06-10-2015

- 2 The proprietor of the food business shall ensure that the requirements of the NSW Food Act 2003, NSW Food Regulation 2010 and the Australian and New Zealand Food Standards Code are met at all times.

- 3 The development shall not be used or occupied until an Occupation Certificate has been issued.

A satisfactory inspection from an authorised officer of Council's Environmental Health Department is required prior to the issue of the Occupation Certificate. The occupier is to contact the Environmental Health Department to organise an appointment at least 72 hours prior to the requested inspection time.

- 4 A **Construction Certificate** shall be obtained prior to commencement of any building works.
- 5 One accessible parking space is to be provided on site with dimensions 2.4m wide with an adjoining 2.4m wide shared zone and bollard. As shown in red on the approved site plan.

### Environmental Matters

- 6 Erosion and sediment control measures shall be installed **prior to the commencement of works on site** including approved clearing of site vegetation. The erosion and sediment control measures are to be maintained in accordance with the approved erosion and sediment control plan(s) for the development and the Department of Housing's "Managing Urban Stormwater: Soils and Construction" 2004.

- 7 The operating noise level of plant and equipment shall not exceed 5dB(A) above the background noise level when measured at the boundaries of the premises. The provisions of the *Protection of the Environment Operations Act 1997* apply to the development, in terms of regulating noise.

## BCA Issues

- 8 The owner of a building, to which an essential fire safety measure is applicable, shall provide Penrith City Council with an annual fire safety statement for the building. The annual fire safety statement for a building must:
- (a) deal with each essential fire safety measure in the building premises, and
  - (b) be given:
    - within 12 months after the last such statement was given, or
    - if no such statement has previously been given, within 12 months after a final fire safety certificate was first issued for the building.
    -
- As soon as practicable after the annual fire safety statement is issued, the owner of the building to which the statement relates:
- must also provide a copy of the statement (together with a copy of the current fire safety schedule) to the Commissioner of New South Wales Fire Brigades, and
  - prominently display a copy of the statement (together with a copy of the current fire safety schedule) in the building.
- 9 All aspects of the building design shall comply with the applicable performance requirements of the Building Code of Australia so as to achieve and maintain acceptable standards of structural sufficiency, safety (including fire safety), health and amenity for the on-going benefit of the community. Compliance with the performance requirements can only be achieved by:
- (a) complying with the deemed to satisfy provisions, or
  - (b) formulating an alternative solution which:
    - complies with the performance requirements, or
    - is shown to be at least equivalent to the deemed to satisfy provision, or
  - (c) a combination of (a) and (b).

It is the owner's responsibility to place on display, in a prominent position within the building at all times, a copy of the latest fire safety schedule and fire safety certificate/ statement for the building.

## Health Matters and OSSM installations

- 10 The construction, fit out and finishes of the food premises must comply with Standard 3.2.3 of the Australian and New Zealand Food Standards Code, and AS4674-2004 *Design, Construction and Fitout of Food Premises*.

- 11 Hand basins must be freestanding, serviced with hot and cold water through a single outlet, able to be mixed at a temperature of at least 40°C and fitted with a hands free operation. Where sensor taps are installed the basin must not be more than 6 metres from the hot water system. Disposable paper hand towels and soap must be provided and serviced from a dispenser adjacent to each hand basin.
- 12 Staff toilets must be provided on the premises.
- 13 A hand basin must be located within the toilet cubicle. Hand basins must be freestanding, serviced with hot and cold water through a single outlet, able to be mixed at a temperature of at least 40°C and fitted with a hands free operation. Where sensor taps are used the basin must not be more than 6 metres from the hot water system. Disposable paper hand towels and soap must be provided and serviced from a dispenser adjacent to each hand basin.
- 14 Hot water services must be positioned at least 75mm clear of the adjacent wall surfaces, and mounted at a minimum 150mm above the floor level on a non-corrosive metal stand. The hot water system must be sized to meet the demands of the food business during peak operating and cleaning periods and be able to provide sufficient hot water throughout the working day. Discharge from the hot water system must enter the sewer through a tongue dish in accordance with Sydney Water's requirements.
- 15 Approved, recessed coving must be provided at all intersections of the floor with the walls within all food preparation, service, storage and scullery areas. All coving must have a minimum concave radius of 25mm and be installed so as to be integral to the surface finish of both floor and wall in such a manner as to form a continuous, uninterrupted surface.
- 16 The ceiling in the preparation, service and scullery areas must be constructed with a rigid, non-absorbent, smooth faced material free from open joints, cracks and crevices and be painted with a light coloured washable paint. The intersection of the walls and ceiling must be tight jointed, sealed and dust proofed. Drop-in panel style ceilings are not permitted.
- 17 Service pipes, electrical conduits, refrigeration condensate pipes shall be enclosed or chased into walls, floors or plinths. Where it can be demonstrated that this is not feasible pipes and conduits fixed on brackets, providing a minimum of 25 mm clearance from the adjacent wall and 100 mm from the floor or adjacent horizontal surface, can be used. All openings in walls, floors and ceilings, through which service pipes and conduits pass, must be vermin proof.
- 18 Appliances used to store potentially hazardous food must have a capacity to keep foods hotter than 60°C, refrigerated foods less than 5°C, and frozen foods less than 18°C and be provided with a digital thermometer, accurate to 1°C that can be easily observed from outside the appliance.
- 19 The meter box must be provided with an approved non-absorbent, smooth faced cover. The cover is to be splayed at an angle of 45 degrees to the wall at the top and made tight fitting to the wall surfaces.
- 20 The drum of the roller door situated in the food preparation area must be enclosed in a frame sheet with compressed cement sheet, and finished smooth and sealed. The enclosure must be accessible for pest control inspection and maintenance.
- 21 Light bulbs or tubes are to be shatterproof or fitted with approved light diffusers (covers or shields) to prevent contamination of food by glass from a broken light globe or tube. Light fittings must be free from any feature that would collect dirt or dust, harbour insects or make the fitting difficult to clean. Light fittings must be recessed into ceilings or equipment where possible. Heat lamps must be protected against breakage by a shield extending beyond the bulb.

- 22 Shelves must be smooth and impervious; free from joints, cracks and crevices; and able to be easily cleaned. The lowest shelf must be at least 200mm off the floor to allow easy cleaning underneath. Approved materials must be used, such as galvanised piping, stainless steel or laminated plastic. Shelves are to be sealed to the wall or kept clear of walls to allow easy access for cleaning (>40 mm).
- 23 The coolroom and/or freezer room floor must be finished with a smooth even surface and graded to the door. A sanitary floor waste must be located outside the coolroom and freezer adjacent to the door. All metal work in the coolroom and freezer room must be treated to resist corrosion.
- 24 Condensation from coolrooms and refrigeration motors must discharge to sewer via a tundish with air gap separation in accordance with Sydney Water requirements.
- 25 The coolroom and freezer room must be provided with:
- A door which can at all times be opened from inside without a key and
  - An approved alarm device located outside the room, but controlled only from the inside.
- 26 The storeroom must be constructed in accordance with AS4674-2004 by providing the following:
- A smooth, even, non-slip floor surface.
  - Coving at all intersections of the floor and walls with approved, recessed coving to a minimum concave radius of 25mm, so as to be integral to the surface finish of both floor and wall in such a manner as to form a continuous, uninterrupted surface. "Feather edge skirting" and non-rebated coving are not permitted.
  - Walls must be provided with a smooth even surface and painted with a light coloured washable paint to enable easy cleaning.
  - The ceiling must be constructed with a rigid, non-absorbent, smooth faced material free from open joints, cracks and crevices and be painted with a light coloured washable paint. The intersections of the walls and ceiling must be tight-jointed, sealed and dustproof. Drop in panel style ceilings are not permitted.
  - Shelving or storage racks must be designed and constructed to enable easy cleaning.
- 27 The business is required to be licensed with the NSW Food Authority under the NSW Food Act 2003 and Food Regulation 2004. A licence shall be obtained prior to commencing operation. Details of this license shall be submitted to Council prior to the commencement of the business, if not supplied by the Food Authority until after the business commenced, within 14 days of the licence being issued.

## Construction

28 Stamped plans, specifications, a copy of the development consent, the Construction Certificate and any other Certificates to be relied upon shall be available on site at all times during construction.

The following details are to be displayed in a maximum of 2 signs to be erected on the site:

- the name of the Principal Certifying Authority, their address and telephone number,
- the name of the person in charge of the work site and telephone number at which that person may be contacted during work hours,
- that unauthorised entry to the work site is prohibited,
- the designated waste storage area must be covered when the site is unattended, and
- all sediment and erosion control measures shall be fully maintained until completion of the construction phase.

Signage but no more than 2 signs stating the above details are to be erected:

- at the commencement of, and for the full length of the, construction works onsite, and
- in a prominent position on the work site and in a manner that can be easily read by pedestrian traffic.

All construction signage is to be removed when the Occupation Certificate has been issued for the development.



29 Prior to the commencement of construction works:

(a) Toilet facilities at or in the vicinity of the work site shall be provided at the rate of one toilet for every 20 persons or part of 20 persons employed at the site. Each toilet provided must be:

- a standard flushing toilet connected to a public sewer, or
- if that is not practicable, an accredited sewage management facility approved by the council, or
- alternatively, any other sewage management facility approved by council.

(b) All excavations and backfilling associated with the erection or demolition of a building must be executed safely and in accordance with the appropriate professional standards. All excavations associated with the erection or demolition of a building must be properly guarded and protected to prevent them from being dangerous to life or property.

(c) If an excavation associated with the erection or demolition of a building extends below the level of the base of the footings of a building on an adjoining allotment of land, the person causing the excavation to be made:

- must preserve and protect the building from damage, and
- if necessary, must underpin and support the building in an approved manner, and
- must, at least 7 days before excavating below the level of the base of the footings of a building on an adjoining allotment of land, give notice of intention to do so to the owner of the adjoining allotment of land and furnish particulars of the excavation to the owner of the building being erected or demolished. The owner of the adjoining allotment of land is not liable for any part of the cost of work carried out for the purposes of this condition, whether carried out on the allotment of land being excavated or on the adjoining allotment of land, (includes a public road and any other public place).

(d) If the work involved in the erection or demolition of a building is likely to cause pedestrian or vehicular traffic in a public place to be obstructed or rendered inconvenient, or involves the enclosure of a public place, hoarding or fence must be erected between the work site and the public place:

- if necessary, an awning is to be erected, sufficient to prevent any substance from, or in connection with, the work falling into the public place,
- the work site must be kept lit between sunset and sunrise if it is likely to be hazardous to persons in the public place, and
- any such hoarding, fence or awning is to be removed when the work has been completed.

30 Construction works or subdivision works that are carried out in accordance with an approved consent that involve the use of heavy vehicles, heavy machinery and other equipment likely to cause offence to adjoining properties shall be restricted to the following hours in accordance with the NSW Environment Protection Authority Noise Control Guidelines:

- Mondays to Fridays, 7am to 6pm
- Saturdays, 7am to 1pm (if inaudible on neighbouring residential premises), otherwise 8am to 1pm
- No work is permitted on Sundays and Public Holidays.

Other construction works carried out inside a building/tenancy and do not involve the use of equipment that emits noise are not restricted to the construction hours stated above.

The provisions of the Protection of the Environment Operations Act, 1997 in regulating offensive noise also apply to all construction works.

## Landscaping

31 Existing landscaping is to be retained and maintained at all times.

## Certification

- 32 Prior to the commencement of any earthworks or construction works on site, the proponent is to:
- (a) employ a Principal Certifying Authority to oversee that the said works carried out on the site are in accordance with the development consent and related Construction Certificate issued for the approved development, and with the relevant provisions of the Environmental Planning and Assessment Act and accompanying Regulation, and
  - (b) submit a Notice of Commencement to Penrith City Council.

The Principal Certifying Authority shall submit to Council an "Appointment of Principal Certifying Authority" in accordance with Section 81A of the Environmental Planning and Assessment Act 1979.

### Information to accompany the Notice of Commencement

Two (2) days before any earthworks or construction/demolition works are to commence on site (including the clearing site vegetation), the proponent shall submit a "Notice of Commencement" to Council in accordance with Section 81A of the Environmental Planning and Assessment Act 1979.

## SIGNATURE

Name:	Gavin Cherry Principal Planner
Signature:	

For the Development Services Manager