NSW RURAL FIRE SERVICE GUIDELINES FOR SINGLE DWELLING DEVELOPMENT APPLICATIONS

SECTION TWO - BUSH FIRE ASSESSMENT REPORT (Attach to DA) PART A **Property Details** Applicants Name: EOGEWATER HOMES Contact Phone Number; (H): (......) 8602 6111 (M): Council: PENSITITCouncil Reference (if known): Lot: 2042 DP: 1168989 Address to be developed: KILLIA WA-1 5000Pu SPRINCS My property is on Bush Fire Prone Land: 🔟 Yes **PART B** Type of Proposal Type of Proposal: △New Building Urban Rural Residential **Dual Occupancy** Isolated Rural Alteration/Additions to an existing building Proposal Description: e.g. two storey house with attached garage ... Stock Stock SUAGRA Copy of plans attached Bush Fire Attack and Level of Construction PARTC Step 1: Asess the vegetation about the proposed building in all directions and convert from Keith to AUSLIG (1990) using SOUTH WEST EAST CATEGORY NORTH Forest Forest Forest Forest Woodland Woodland Woodland Woodland Shrubland Shrubland Shrubland Shrubland Scrub Scrub Scrub Scrub Mallee/Mulga Mallee/Mulga Mallee/Mulga Mallee/Mulga Converted vegetation Rainforest Rainforest Rainforest Rainforest Tussock Tussock Tussock Tussock Moorland Moorland Moorland Moorland Managed Lar Copy of any relevant photos attached Step 2: Determine the distance from the building line to the vegetation in each direction as above WEST EAST SOUTH NORTH **ASPECT**

400

100

Step 3: Determine the effective slope that will influence bushfire behaviour in each direction

CATEGORY	NORTH	EAST	SOUTH	WEST			
Slope under the hazard (over 100m) [in degrees]	upslope/flat >0 to 5 >5 to 10 >10 to 15 >15 to 18	upslope/flat >0 to 5 >5 to 10 >10 to 15 >15 to 18	upslope/flat >0 to 5 >5 to 10 >10 to 15 >15 to 18	upslope/flat >0 to 5 >5 to 10 >10 to 15 >15 to 18			
Step 4: Determine the Fire Danger Index (FDI) that applies to your local government area (see page 9). Circle the relevant FDI below							
FDI	⋈ 100	80		50			
Step 5: Match the relevant FDI, vegetation, distance and slope to determine the required APZ and Construction level							
FDI	100 (see Table 4, page 1	1) 80 (see Tab	ole 5. page 12)	50 (see Table 6. page 13)			
Identify the bush fire attack level for each direction, select the highest level for the entire building and record below. Note BAL-12.5 is the lowest construction level within the scope of AS3959. Bush Fire Attack Level BAL- FZ BAL- 19 BAL- 40 BAL- 29 No requirement Does your proposal meet the required construction level YES NO							
boos your proposarmeet the req	an ca construction (cr						

If you determine your house is located in the flame zone you may wish to seek the advice of a specialist bush fire consultant.

PARTE	Water Supplies					
Does your property h to the nearest fire hyd		d (piped) water supply?; If so, please provide detaite plan.	ls on the distance			
Reticulated (piped) w	rater supply is a	vailable				
Yes No D	Distance	(m) to hydrant from house.				
Do you have or do yo	u plan to have a	a dedicated water supply for firefighting purposes	?			
□ _{Yes} □ _{No}						
Development Type	more (Filestra)	Water Requirement	Planned	Existing		
Residential Lots (<1,000m2)		5,000 l/lot	-			
Rural-residential Lots (1,000–10,000m2)		10,000 I/lot				
Large Rural/Lifestyle Lots (>10,000m2)		20,000 I/lot				
Dual Occupancy		2,500 l/unit				
Townhouse/Unit Style (e.g	. Flats)	5,000 l/unit up to 20,000l maximum	-			
Do you have or do you litres and also include Water supply type	u plan to have a tank material if Capacity	static water supply (e.g. pool, tank or dam). Include using a tank: Construction material	de approx. size in	Existing		
e.g. pool	50,0001	Above ground rolled steel with plastic liner				
	- P					
NOTE: Check with you Control Plan (DCP) as 1	r local council c his may dictate	oncerning their Local Environmental Plan (LEP) or the type and size of tank.	their Development			
PART F	Ga	s Supplies				
GAS Do you have reticulate	d (piped) or bo	ttled gas?				



TYPE OF GAS Reticulated gas Bottled gas