NatHERS Assessment Summary

Project Details	Address: Lot 300	8 Lord Sheffield Circuit, Penrith, NSW, 2750
	Lot and Plan: 300	08
	Council: Penrith	City Council
	NCC Climate Zon	e: 5
	Project Descripti	on: Unit Building (48 Units)
	Building Classific	ation: 2
Result	Complies with m	aximum heating and cooling loads in BASIX
Construction Details and	External Walls:	Brick veneer
Minimum Requirements	Insulation:	R1.5 batts
	Internal Walls:	Plasterboard
	Insulation:	N/A
	Floor:	Suspended slab
	Insulation:	N/A
	Ceiling:	Plasterboard
	Insulation:	R3.0 batts to top level ceiling
	Roof:	Concrete slab
	Insulation:	N/A
	Glazing:	Standard: Low-e glazing (Max. U value 5.4, SHGC between 0.55-0.61)
		Unit 802: Max. U value 4.3, SHGC between 0.50-0.56
		Unit 803: Max. U value 4.8, SHGC between 0.56-0.62
	Ceiling Penetrations:	Sealed exhaust fans
	Other:	N/A

Document Set ID: 9129545 Version: 1, Version Date: 08/05/2020

Nationwide House Energy Rating Scheme* — Class 2 summary

Certificate Date: 24 Feb 2020 Certificate number: 0004617100 ★ Average Star rating: **6.5**



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

conor.horwood@accsa.net.au Email:

Phone: 07 3069 5757

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: **BDAV**

Dwelling details

Street: **Lot 3008 Lord Sheffield Circuit**

Suburb: **Penrith** State: **NSW** Postcode: 2750

Scan to access this certificate online and confirm this is valid.





Summary of all dwellings

Certificate Details					
Certificate number	Unit number	Heating load	Cooling load	Total load	Star Rating
0004616488-01	301	20.2	45.1	65.3	7.1
0004616728-01	302	50.4	40.0	90.4	5.9
0004616694-01	303	49.2	57.2	106.4	5.3
0004616660-01	304	37.4	43.8	81.2	6.3
0004616637-01	305	31.4	33.5	64.9	7.1
0004616603-02	306	17.1	49.6	66.7	6.9
0004616579-01	307	18.1	48.4	66.6	6.9
0004616546-01	308	17.6	62.7	80.3	6.4
0004616512-01	401	24.7	32.1	56.8	7.4
0004616454-02	402	57.3	31.6	89.0	5.9
0004616421-01	403	50.9	51.4	102.3	5.4
0004616397-01	404	40.5	38.9	79.4	6.4
0004616371-01	405	34.7	29.0	63.7	7.2
0004616348-01	406	25.8	54.1	79.9	6.4
0004616314-01	407	20.5	45.4	65.9	7

Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Nationwide House Energy Rating Scheme* - Class 2 summary

Certificate number: **0004617100** Certificate Date:

24 Feb 2020

★ Average Star rating: 6.5



Summary of all dwellings continued

Certificate number	Unit number	Heating load	Cooling load	Total load	Star Rating
0004616298-02	408	18.0	40.3	58.3	7.4
0004616744-01	501	25.1	31.7	56.9	7.4
0004616702-01	502	57.9	32.0	89.8	5.9
0004616678-01	503	51.6	51.1	102.7	5.4
0004616645-01	504	41.0	38.7	79.7	6.4
0004616611-01	505	35.1	28.7	63.7	7.2
0004616363-01	506	26.3	52.4	78.7	6.4
0004616587-01	507	20.9	45.2	66.2	6.9
0004616561-02	508	18.4	40.2	58.6	7.4
0004616520-01	601	25.4	31.6	57.0	7.4
0004616496-01	602	58.3	31.8	90.1	5.9
0004616462-02	603	52.0	50.7	102.8	5.4
0004616439-02	604	41.4	38.6	80.0	6.4
0004616405-01	605	35.4	28.4	63.9	7.1
0004616330-01	606	26.5	51.9	78.3	6.4
0004616306-01	607	21.3	45.0	66.2	6.9
0004616272-01	608	18.6	39.8	58.5	7.4
0004616736-01	701	25.7	31.5	57.2	7.4
0004616710-01	702	58.7	31.8	90.5	5.9
0004616686-01	703	52.5	50.8	103.2	5.4
0004616652-01	704	41.8	38.4	80.1	6.4
0004616629-01	705	35.8	28.2	64.0	7.1
0004616595-02	706	26.7	51.8	78.5	6.4
0004616553-01	707	21.6	44.5	66.1	6.9
0004616538-01	708	18.9	39.9	58.8	7.4
0004616504-01	801	40.9	36.5	77.4	6.4
0004616470-01	802	56.6	31.3	88.0	5.9
0004616447-02	803	57.6	53.5	111.1	5.1
0004616413-01	804	57.7	41.7	99.4	5.4
0004616389-01	805	52.4	33.1	85.5	6.1
0004616355-01	806	43.0	57.9	100.9	5.4
0004616322-01	807	35.3	49.8	85.2	6.1
0004616280-02	808	32.7	45.3	78.0	6.4

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Nationwide House Energy Rating Scheme* — Class 2 summary

Certificate Date: 24 Feb 2020 Certificate number: 0004617100 ★ Average Star rating: **6.5**



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

conor.horwood@accsa.net.au Email:

Phone: 07 3069 5757

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: **BDAV**

Dwelling details

Street: **Lot 3008 Lord Sheffield Circuit**

Suburb: **Penrith** State: **NSW** Postcode: 2750

Scan to access this certificate online and confirm this is valid.





Summary of all dwellings

Certificate Details					
Certificate number	Unit number	Heating load	Cooling load	Total load	Star Rating
0004616488-01	301	20.2	45.1	65.3	7.1
0004616728-01	302	50.4	40.0	90.4	5.9
0004616694-01	303	49.2	57.2	106.4	5.3
0004616660-01	304	37.4	43.8	81.2	6.3
0004616637-01	305	31.4	33.5	64.9	7.1
0004616603-02	306	17.1	49.6	66.7	6.9
0004616579-01	307	18.1	48.4	66.6	6.9
0004616546-01	308	17.6	62.7	80.3	6.4
0004616512-01	401	24.7	32.1	56.8	7.4
0004616454-02	402	57.3	31.6	89.0	5.9
0004616421-01	403	50.9	51.4	102.3	5.4
0004616397-01	404	40.5	38.9	79.4	6.4
0004616371-01	405	34.7	29.0	63.7	7.2
0004616348-01	406	25.8	54.1	79.9	6.4
0004616314-01	407	20.5	45.4	65.9	7

Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Nationwide House Energy Rating Scheme* - Class 2 summary

Certificate number: **0004617100** Certificate Date:

24 Feb 2020

★ Average Star rating: 6.5



Summary of all dwellings continued

Certificate number	Unit number	Heating load	Cooling load	Total load	Star Rating
0004616298-02	408	18.0	40.3	58.3	7.4
0004616744-01	501	25.1	31.7	56.9	7.4
0004616702-01	502	57.9	32.0	89.8	5.9
0004616678-01	503	51.6	51.1	102.7	5.4
0004616645-01	504	41.0	38.7	79.7	6.4
0004616611-01	505	35.1	28.7	63.7	7.2
0004616363-01	506	26.3	52.4	78.7	6.4
0004616587-01	507	20.9	45.2	66.2	6.9
0004616561-02	508	18.4	40.2	58.6	7.4
0004616520-01	601	25.4	31.6	57.0	7.4
0004616496-01	602	58.3	31.8	90.1	5.9
0004616462-02	603	52.0	50.7	102.8	5.4
0004616439-02	604	41.4	38.6	80.0	6.4
0004616405-01	605	35.4	28.4	63.9	7.1
0004616330-01	606	26.5	51.9	78.3	6.4
0004616306-01	607	21.3	45.0	66.2	6.9
0004616272-01	608	18.6	39.8	58.5	7.4
0004616736-01	701	25.7	31.5	57.2	7.4
0004616710-01	702	58.7	31.8	90.5	5.9
0004616686-01	703	52.5	50.8	103.2	5.4
0004616652-01	704	41.8	38.4	80.1	6.4
0004616629-01	705	35.8	28.2	64.0	7.1
0004616595-02	706	26.7	51.8	78.5	6.4
0004616553-01	707	21.6	44.5	66.1	6.9
0004616538-01	708	18.9	39.9	58.8	7.4
0004616504-01	801	40.9	36.5	77.4	6.4
0004616470-01	802	56.6	31.3	88.0	5.9
0004616447-02	803	57.6	53.5	111.1	5.1
0004616413-01	804	57.7	41.7	99.4	5.4
0004616389-01	805	52.4	33.1	85.5	6.1
0004616355-01	806	43.0	57.9	100.9	5.4
0004616322-01	807	35.3	49.8	85.2	6.1
0004616280-02	808	32.7	45.3	78.0	6.4

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616488-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7.1



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: **BERS Pro v4.4.0.0 (3.21)**

AAO: BDAV

Overview

Dwelling details

Street: Unit 301, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

Lot/DP

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

climate zone: 28

number: 3008/- Exposure: Suburban

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 78.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 83.0


Annual thermal performance loads (MJ/m²)

Heating: 20.2 Cooling: 45.1 TOTAL: 65.3

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616488-01** Certificate Date: **24**

24 Feb 2020 ★ Star rating:



Building features

Window type and performance value					
Window ID	Window type	U-value	SHGC		
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58		

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2700	NE	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	SE	Awning
Bedroom 1	ALM-002-03 A	n/a	1800	900	NW	No Shading
Bedroom 2	ALM-002-03 A	n/a	1800	900	SE	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	3600	NE	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	1500	NE	No Shading
Ens	ALM-002-03 A	n/a	1800	900	SE	Awning

ID	Window	type		U-value	SHGC
None Presen	t				
Roof windo	w and skyligh	nt schedule			
-1001 Williao	ii ana okyngi				

ID	Wall type		Insulation W			all wrap or foil		
EW-1	Brick Veneer	Bulk Insulation R1.5		No				
External wall schedule								
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)		
Bedroom 1	EW-1	2800	2790	NE	No	0		
Bedroom 1	EW-1	335	2790	Е	No	0		
Bedroom 1	EW-1	320	2790	E	No	0		
Bedroom 1	EW-1	3245	2790	SE	No	0		
Bedroom 1	EW-1	1150	2790	NW	No	7050		
Bedroom 2	EW-1	2795	2790	SE	No	0		
Bedroom 2	EW-1	762	2790	SW	No	56		
Bedroom 2	EW-1	610	2790	S	No	25		
Kitchen/Living	EW-1	5945	2790	NE	No	1150		
Kitchen/Living	EW-1	2600	2790	NW	No	1100		
Ens	EW-1	2840	2790	SE	No	0		

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
	61.0	No insulation	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616488-01 Certificate Date: 24 Feb 2020

★ Star rating:



Building features continued

IW-1 - Cavity wall, direct fix plasterboard, single gap

IW-2 - Shaft liner party wall with 41.0 Bulk Insulation both sides of shaft liner R1.5 No

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	5.0	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	13.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.7	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	47.3	None	No Insulation	Cork Tiles or Parquetry 8mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed	
Bath	1	Exhaust Fans	300	Sealed	
Kitchen/Living	1	Exhaust Fans	300	Sealed	
Ens	1	Exhaust Fans	300	Sealed	

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

For more information on the Nationwide House Energy Rating Scheme (NatHERS), visit www.nathers.gov.au For more information on energy efficient design and insulation visit www.yourhome.gov.au

Certificate number: 0004616728-01 Certificate Date: 24 Feb 2020 ★ Star rating: 5.9



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 302, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

Lot/DP

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

climate zone: 28

number: 3008/- Exposure: Suburban

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 71.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 76.0


Annual thermal performance loads (MJ/m²)

Heating: **50.4** Cooling: **40.0** TOTAL: **90.4**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

Unsealed: 0
TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616728-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2700	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	3700	SW	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	SE	Awning
Bedroom 1	ALM-002-03 A	n/a	1800	750	SW	Awning
Bedroom 1	ALM-002-03 A	n/a	1800	1500	SW	No Shading
Ens	ALM-002-03 A	n/a	1800	900	SE	No Shading
Ens	ALM-002-03 A	n/a	1800	900	SE	No Shadin

ID	Window	type			U-value	SHGC
None Presen	t					
Roof windo	w and skyligh	nt schedule				
Location	ID	Roof	A / 2\	Ovientation	Outdoor shade	Indoor

External wall type			
ID	Wall type	Insulation	Wall wrap or foil
EW-1	Brick Veneer	Bulk Insulation R1.5	No
EW-2	Brick Veneer	Foil, Anti-glare one side, Reflective other	Yes

External wall schedule

Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	2995	2790	SW	No	2925
Kitchen/Living	EW-1	3995	2790	SW	No	1175
Kitchen/Living	EW-1	1750	2790	NW	No	4725
Bedroom 1	EW-1	1150	2790	NW	No	8675
Bedroom 1	EW-1	4845	2790	SE	No	0
Bedroom 1	EW-1	707	2790	S	No	0
Bedroom 1	EW-1	2600	2790	SW	No	0
Ens	EW-1	2240	2790	SE	No	0
Bath	EW-1	1242	2790	Е	No	0
Bath	EW-1	895	2790	SE	No	0

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Cavity wall, direct fix plasterboard, single gap	61.0	No insulation	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616728-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

IW-2 - Shaft liner party wall with 43.0 Bulk Insulation both sides of shaft liner R1.5 No

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.4	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	39.5	None	No Insulation	Cork Tiles or Parquetry 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above	
Bedroom 2	Concrete, Plasterboard	No insulation	No	
Kitchen/Living	Concrete, Plasterboard	No insulation	No	
Bedroom 1	Concrete, Plasterboard	No insulation	No	
Ens	Concrete, Plasterboard	No insulation	No	
Bath	Concrete, Plasterboard	No insulation	No	

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Kitchen/Living	1	Exhaust Fans	300	Sealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

For more information on the Nationwide House Energy Rating Scheme (NatHERS), visit www.nathers.gov.au For more information on energy efficient design and insulation visit www.yourhome.gov.au

Certificate number: **0004616694-01** Certificate Date: 24 Feb 2020 ★ Star rating: **5.3**



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: 07 3069 5757

Declaration None

of interest:

BERS Pro v4.4.0.0 (3.21) Software:

BDAV AAO:

Overview

Dwelling details

Unit 303, Lot 3008 Lord Sheffield Circuit Street:

Suburb: Penrith

Lot/DP

Postcode: State: **NSW** 2750 NCC Class: 2 **New Dwelling** Type:

NatHERS

climate zone: 28

number: 3008/-Exposure: Suburban

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

> No ceiling insulation No floor insulation

ALM-002-03 A Aluminium B SG High Glazing:

Solar Gain Low-E

Net floor area (m²)

Conditioned: 44.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 48.0


Annual thermal performance loads (MJ/m²)

Heating: 49.2 Cooling: 57.2 TOTAL: 106.4

Plan documents

11749, Revision E Plan ref/date:

Prepared by: **DKO**



Ceiling penetrations

Sealed: Unsealed: 0

TOTAL:** 2

**NOTE: This total is the maximum number of ceiling (see following pages for details) penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616694-01** Certificate Date: 24 Feb 2020

★ Star rating:



5.3

Building features

Window type	and performand	e value				
Window ID	Window type				U-value	SHGC
ALM-002-03 A	ALM-002-03 A	Aluminium B SG	High Solar Gain	Low-E	5.4	0.58
Window sche	dule					
Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	3300	SW	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	2400	NW	No Shading

Roof windo	w and skylight typ	e and performanc	e value			
None Presen	Window type				U-value	SHGC
Roof windo	w and skylight sc	hedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Presen	t					

ID	Wall type		Insulation		Wa	II wrap or fo
EW-1	Brick Veneer		Bulk Insulation R1.5		No	
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	2995	2790	SW	No	2600
Kitchen/Living	EW-1	2850	2790	SE	No	3025
Kitchen/Living	EW-1	3700	2790	SW	No	0
Kitchen/Living	EW-1	2600	2790	NW	No	4450

Internal wall type				
Wall type	Area (m²)	Insulation	Wall wrap or foil	
IW-1 - Shaft liner party wall with plaster	51.0	Bulk Insulation both sides of shaft liner R1.5	No	
IW-2 - Cavity wall, direct fix plasterboard, single gap	25.0	No insulation	No	

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	4.2	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below	12.1	None	No Insulation	Carpet+Rubber

Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616694-01** Certificate Date:

24 Feb 2020

★ Star rating:



5.3

Building features continued

	250mm				Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	31.7	None	No Insulation	Cork Tiles or Parquetry 8mm

Ceiling type			
Location	Construction	Added insulation	Roof space above
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Construction	Added Roof cold insulation
None Present	

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

For more information on the Nationwide House Energy Rating Scheme (NatHERS), visit www.nathers.gov.au For more information on energy efficient design and insulation visit www.yourhome.gov.au

Certificate number: 0004616660-01 Certificate Date: 24 Feb 2020 ★ Star rating: 6.3



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: **BERS Pro v4.4.0.0 (3.21)**

AAO: BDAV

Overview

Dwelling details

Street: Unit 304, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

Lot/DP

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

climate zone: 28

number: 3008/- Exposure: Suburban

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 49.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 53.0


Annual thermal performance loads (MJ/m²)

Heating: **37.4** Cooling: **43.8** TOTAL: **81.2**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 2

Unsealed: 0
TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616660-01 Certificate Date: 24 Feb 2020

★ Star rating:



6.3

Building features

window type a	and performance value			
Window ID	Window type	U-value	SHGC	
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58	

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	1200	W	Awning
Kitchen/Living	ALM-002-03 A	n/a	1800	3300	W	Awning

ID	Window type				U-value	SHGC
None Present	,, , , , , , , , , , , , , , , , , , ,					
Roof window	and skylight sch	edule				
Location	ID	Roof	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	3445	2790	SW	No	1950
Kitchen/Living	EW-1	1882	2790	S	No	2247
Kitchen/Living	EW-1	1956	2790	W	No	0
Kitchen/Living	EW-1	3824	2790	W	No	0

Internal wall type					
Wall type	Area (m²)	Insulation	Wall wrap or foil		
IW-1 - Shaft liner party wall with plaster	54.0	Bulk Insulation both sides of shaft liner R1.5	No		
IW-2 - Cavity wall, direct fix plasterboard, single gap	26.0	No insulation	No		

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	13.2	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below	4.3	None	No Insulation	Ceramic Tiles

Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616660-01 Certificate Date: 24 I

24 Feb 2020 ★ Star rating:



6.3

Building features continued

Kitchen/Living Concrete Slab, Unit Below 35.4 None No Insulation Cork Tiles or Parquetry 8mm		250mm				8mm
	Kitchen/Living		35.4	None	No Insulation	

Ceiling type			
Location	Construction	Added insulation	Roof space above
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations				
Number	Туре	Diameter (mm)	Sealed/unsealed	
1	Exhaust Fans	300	Sealed	
1	Exhaust Fans	300	Sealed	
		NumberType1Exhaust Fans	NumberTypeDiameter (mm)1Exhaust Fans300	

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Construction	Added Roof colou insulation
None Present	

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

For more information on the Nationwide House Energy Rating Scheme (NatHERS), visit www.nathers.gov.au For more information on energy efficient design and insulation visit www.yourhome.gov.au

Certificate number: 0004616637-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7.1



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 305, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Suburban

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 69.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 74.0


Annual thermal performance loads (MJ/m²)

Heating: **31.4** Cooling: **33.5** TOTAL: **64.9**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:** 3

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616637-01 Certificate Date: 24 Fe

24 Feb 2020 ★ Star rating:



Building features

Window type and performance value

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2400	W	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	2000	W	Awning
Kitchen/Living	ALM-002-03 A	n/a	1800	3000	W	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	2700	N	No Shading

Roof window	w and skyligh	t type and performanc	e value			
None Present	Window	type			U-value	SHGC
Roof window	w and skyligh	t schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present						

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No	1
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	3010	2790	W	No	3121
Bedroom 1	EW-1	3005	2790	W	No	0
Kitchen/Living	EW-1	4031	2790	W	No	0
Kitchen/Living	EW-1	3157	2790	N	No	4887

Internal wall type					
Wall type	Area (m²)	Insulation	Wall wrap or foil		
IW-1 - Shaft liner party wall with plaster	67.0	Bulk Insulation both sides of shaft liner R1.5	No		
IW-2 - Cavity wall, direct fix plasterboard, single gap	55.0	No insulation	No		

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

24 Feb 2020 Certificate number: **0004616637-01** Certificate Date: ★ Star rating:



Building featur	es continued				
Bedroom 2	Concrete Slab, Unit Below 250mm	10.7	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	4.9	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	15.3	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	37.4	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations					
Number	Туре	Diameter (mm)	Sealed/unsealed		
1	Exhaust Fans	300	Sealed		
1	Exhaust Fans	300	Sealed		
1	Exhaust Fans	300	Sealed		
		NumberType1Exhaust Fans1Exhaust Fans	NumberTypeDiameter (mm)1Exhaust Fans3001Exhaust Fans300		

Ceiling fans			
Location	Number	Diameter (mm)	
None Present	2		

Roof type		
Construction	Added insulation	Roof colour
None Present		-

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

For more information on the Nationwide House Energy Rating Scheme (NatHERS), visit www.nathers.gov.au For more information on energy efficient design and insulation visit www.yourhome.gov.au

Certificate number: **0004616603-02** Certificate Date: 24 Feb 2020 ★ Star rating: 6.9



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: 07 3069 5757

Declaration None

of interest:

BERS Pro v4.4.0.0 (3.21) Software:

BDAV AAO:

Overview

Dwelling details

Unit 306, Lot 3008 Lord Sheffield Circuit Street:

Suburb: Penrith

Postcode: State: **NSW** 2750 NCC Class: 2 Type:

New Dwelling NatHERS

climate zone: 28 Lot/DP

number: 3008/-Exposure: Suburban

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

> No ceiling insulation No floor insulation

ALM-002-03 A Aluminium B SG High Glazing:

Solar Gain Low-E

Net floor area (m²)

Conditioned: 73.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 78.0


Annual thermal performance loads (MJ/m²)

Heating: 17.1 Cooling: 49.6 TOTAL: 66.7

Plan documents

11749, Revision E Plan ref/date:

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3 Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616603-02 Certificate Date: 24 Fe

24 Feb 2020 ★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	900	N	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	No Shading
Bedroom 2	ALM-002-03 A	n/a	2700	2400	W	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	3600	W	No Shading

Roof windo	w and skyligh	nt type and performanc	e value			
None Present	Window t	type			U-value	SHGC
Roof windo	w and skyligh	nt schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present	t					

ID	Wall type		Insulation		Wa	all wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall schedule						
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	3081	2790	W	No	35
Bedroom 1	EW-1	5447	2790	N	No	35
Bedroom 1	EW-1	1092	2790	S	No	8596
Ens	EW-1	2220	2790	N	No	35
Bedroom 2	EW-1	3005	2790	W	No	2975
Bath	EW-1	917	2790	N	No	0
Bath	EW-1	743	2790	Е	No	0
Bath	EW-1	618	2790	NE	No	0
Kitchen/Living	EW-1	1835	2790	S	No	4405
Kitchen/Living	EW-1	4102	2790	W	No	1134

Internal wall type				
Wall type	Area (m²)	Insulation	Wall wrap or foil	
IW-1 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No	
IW-2 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No	

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616603-02** Certificate Date: **24 Feb 2020**

20 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	16.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bedroom 2	Concrete Slab, Unit Below 250mm	10.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	4.5	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	40.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations					
Location	Number	Туре	Diameter (mm)	Sealed/unsealed	
Ens	1	Exhaust Fans	300	Sealed	
Bath	1	Exhaust Fans	300	Sealed	
Kitchen/Living	1	Exhaust Fans	300	Sealed	

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		-

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

For more information on the Nationwide House Energy Rating Scheme (NatHERS), visit www.nathers.gov.au For more information on energy efficient design and insulation visit www.yourhome.gov.au

Certificate number: 0004616579-01 Certificate Date: 24 Feb 2020 ★ Star rating: 6.9



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 307, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Suburban

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 74.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 79.0


Annual thermal performance loads (MJ/m²)

Heating: 18.1 Cooling: 48.4 TOTAL: 66.6

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616579-01 Certificate Date: 24 Feb 2020

★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2400	E	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	2400	E	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	3900	Е	No Shading

Roof windo	w and skyligl	nt type and performanc	e value			
None Presen	Window t	type			U-value	SHGC
Roof windo	w and skyligl	nt schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Presen	t					

ID	Wall type		Insulation		Wa	II wrap or foi	
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)	
External wall schedule							
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 2	EW-1	3043	2790	E	No	3173	
Bedroom 1	EW-1	1129	2790	S	No	11336	
Bedroom 1	EW-1	2296	2790	N	No	0	
Bedroom 1	EW-1	3250	2790	N	No	25	
Bedroom 1	EW-1	2512	2790	E	No	71	
Ens	EW-1	2257	2790	N	No	0	
Bath	EW-1	1315	2790	NW	No	25	
Bath	EW-1	846	2790	N	No	35	
Kitchen/Living	EW-1	4111	2790	Е	No	1207	
Kitchen/Living	EW-1	1980	2790	S	No	6947	

Internal wall type				
Wall type	Area (m²)	Insulation	Wall wrap or foil	
IW-1 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No	
IW-2 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No	

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616579-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.5	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 1	Concrete Slab, Unit Below 250mm	15.8	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.6	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	41.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations			
Number	Туре	Diameter (mm)	Sealed/unsealed
1	Exhaust Fans	300	Sealed
1	Exhaust Fans	300	Sealed
1	Exhaust Fans	300	Sealed
		NumberType1Exhaust Fans1Exhaust Fans	NumberTypeDiameter (mm)1Exhaust Fans3001Exhaust Fans300

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		-

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

For more information on the Nationwide House Energy Rating Scheme (NatHERS), visit www.nathers.gov.au For more information on energy efficient design and insulation visit www.yourhome.gov.au

Certificate number: 0004616546-01 Certificate Date: 24 Feb 2020 ★ Star rating: 6.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 308, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Suburban

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 73.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 78.0


Annual thermal performance loads (MJ/m²)

Heating: 17.6 Cooling: 62.7 TOTAL: 80.3

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616546-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features

Window type a	and performance value		
Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	1800	E	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	NE	No Shading
Bedroom 2	ALM-002-03 A	n/a	2700	2400	Е	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	3900	E	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	2700	N	No Shading

Window t	уре			U-value	SHGC
w and skylight	schedule				
ID	Roof window/skylight	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
	w and skylight	v and skylight schedule ID Roof	v and skylight schedule ID Roof Area (m²)	v and skylight schedule ID Roof Area (m²) Orientation	v and skylight schedule ID Roof Area (m²) Orientation Outdoor shade

ID	Wall type		Insulation		Wa	II wrap or fo	
EW-1	Brick Veneer		Bulk Insulation	Bulk Insulation R1.5		No	
External wall schedule							
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 1	EW-1	1846	2790	Е	No	90	
Bedroom 1	EW-1	912	2790	NE	No	25	
Bedroom 1	EW-1	600	2790	NE	No	50	
Bedroom 2	EW-1	3073	2790	E	No	3078	
Kitchen/Living	EW-1	4172	2790	Е	No	106	
Kitchen/Living	EW-1	3015	2790	N	No	5508	

Internal wall type				
Wall type	Area (m²)	Insulation	Wall wrap or foil	
IW-1 - Shaft liner party wall with plaster	71.0	Bulk Insulation both sides of shaft liner R1.5	No	
IW-2 - Cavity wall, direct fix plasterboard, single gap	57.0	No insulation	No	

Floors

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616546-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Ens	Concrete Slab, Unit Below 250mm	5.9	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.5	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	5.1	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	38.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 401, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 74.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 79.0

Annual thermal performance loads (MJ/m²)

 Heating:
 24.7


 Cooling:
 32.1

 TOTAL:
 56.8

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:** 3

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616512-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	900	NE	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	SE	Awning
Bedroom 1	ALM-002-03 A	n/a	2700	1800	NW	No Shading
Bedroom 2	ALM-002-03 A	n/a	1800	900	SE	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	3600	NE	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	1500	NE	No Shading
Ens	ALM-002-03 A	n/a	1800	900	SE	Awning

ID	Window	type		U-value	SHGC
None Presen	t				
Roof windo	w and skyligh	nt schedule			

ID	Wall type		Insulation W			all wrap or foil	
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)	
External wall	schedule						
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 1	EW-1	2800	2790	NE	No	0	
Bedroom 1	EW-1	335	2790	Е	No	0	
Bedroom 1	EW-1	320	2790	E	No	0	
Bedroom 1	EW-1	3245	2790	SE	No	0	
Bedroom 1	EW-1	1850	2790	NW	No	7050	
Bedroom 2	EW-1	2795	2790	SE	No	0	
Bedroom 2	EW-1	762	2790	SW	No	40	
Bedroom 2	EW-1	610	2790	S	No	18	
Kitchen/Living	EW-1	5945	2790	NE	No	1850	
Kitchen/Living	EW-1	1900	2790	NW	No	1113	
Ens	EW-1	2840	2790	SE	No	0	

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
	59.0	No insulation	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616512-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

IW-1 - Cavity wall, direct fix plasterboard, single gap

IW-2 - Shaft liner party wall with 41.0 Bulk Insulation both sides of shaft liner R1.5 No

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	5.0	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	13.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.7	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	43.1	None	No Insulation	Cork Tiles or Parquetry 8mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed
Ens	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information		

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616454-02 Certificate Date: 24 Feb 2020 ★ Star rating: 5.9



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 402, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 71.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 76.0


Annual thermal performance loads (MJ/m²)

Heating: 57.3 Cooling: 31.6 TOTAL: 89.0

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3

Unsealed: 0
TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616454-02 Certificate Date: 24 Feb 2020

★ Star rating:



Building features

Window type a	and performance value		
Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2700	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	3700	SW	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	SE	Awning
Bedroom 1	ALM-002-03 A	n/a	1800	2350	SW	Awning
Ens	ALM-002-03 A	n/a	1800	900	SE	Awning

ID	Window type	е			U-value	SHGC
None Present						
Roof window	w and skylight so	chedule				
Location	ID	Roof	Area (m²)	Orientation	Outdoor shade	Indoor

ID	Wall type		Insulation		W	all wrap or foi
EW-1	Brick Veneer		Bulk Insulation	Bulk Insulation R1.5		
EW-2	Brick Veneer		Foil, Anti-glare	e one side, Refle	ctive other Y	es
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	2995	2790	SW	No	2925
Kitchen/Living	EW-1	3995	2790	SW	No	1175
Kitchen/Living	EW-1	1750	2790	NW	No	4725
Bedroom 1	EW-1	1150	2790	NW	No	8675
Bedroom 1	EW-1	4845	2790	SE	No	0
Bedroom 1	EW-1	707	2790	S	No	0
Bedroom 1	EW-1	2600	2790	SW	No	0
Ens	EW-1	2240	2790	SE	No	0
Bath	EW-1	1242	2790	Е	No	0
Bath	EW-1	895	2790	SE	No	0

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Cavity wall, direct fix plasterboard, single gap	61.0	No insulation	No
IW-2 - Shaft liner party wall with	43.0	Bulk Insulation both sides of shaft liner R1.5	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616454-02** Certificate Date:

24 Feb 2020 ★ Star rating:



Building features continued

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.4	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	39.5	None	No Insulation	Cork Tiles or Parquetry 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 2	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Kitchen/Living	1	Exhaust Fans	300	Sealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed

Location Number Diameter (mm)	
None Present	

Roof type		
Construction	Added insulation	Roof colour
None Present		-

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616421-01 Certificate Date: 24 Feb 2020 ★ Star rating: 5.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 403, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 44.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 48.0


Annual thermal performance loads (MJ/m²)

Heating: 50.9
Cooling: 51.4
TOTAL: 102.3

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 2

Unsealed: 0
TOTAL:***

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616421-01 Certificate Date: 24 Feb 2020 ★

★ Star rating:



Building features

Window type and	I performance value
-----------------	---------------------

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	2100	SW	Awning
Kitchen/Living	ALM-002-03 A	n/a	1800	900	SW	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	2400	NW	No Shading

Roof window and skylight type and performance value						
None Present	Window type				U-value	SHGC
Roof window and skylight schedule						
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present			-			

ID	Wall type		Insulation		Wa	II wrap or foi	
EW-1	Brick Veneer	k Veneer		Bulk Insulation R1.5		No	
External wall s	schedule						
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 1	EW-1	2995	2790	SW	No	2600	
Kitchen/Living	EW-1	2850	2790	SE	No	3025	
Kitchen/Living	EW-1	3700	2790	SW	No	0	
Kitchen/Living	EW-1	2600	2790	NW	No	4450	

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	51.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	25.0	No insulation	No

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	4.2	None	No Insulation	Ceramic Tiles 8mm

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

24 Feb 2020 Certificate number: **0004616421-01** Certificate Date: ★ Star rating:



Building featui	res continued				
Bedroom 1	Concrete Slab, Unit Below 250mm	12.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	31.7	None	No Insulation	Cork Tiles or Parquetry 8mm

Ceiling type			
Location	Construction	Added insulation	Roof space above
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No
Tatorion/Living	- Ochorete, Flasterboard	- IVO IIISUIAUOII	110

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type		
Construction	Added Roof colou insulation	ır
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: **0004616397-01** Certificate Date: 24 Feb 2020 ★ Star rating: 6.4



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: 07 3069 5757

Declaration None

of interest:

BERS Pro v4.4.0.0 (3.21) Software:

BDAV AAO:

Overview

Dwelling details

Unit 404, Lot 3008 Lord Sheffield Circuit Street:

Suburb: Penrith

Postcode: State: **NSW** 2750 NCC Class: 2 **New Dwelling** Type:

NatHERS

climate zone: 28 Lot/DP

number: 3008/-Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

> No ceiling insulation No floor insulation

ALM-002-03 A Aluminium B SG High Glazing:

Solar Gain Low-E

Net floor area (m²)

Conditioned: 49.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 53.0


Annual thermal performance loads (MJ/m²)

Heating: 40.5 Cooling: 38.9 TOTAL: 79.4

Plan documents

11749, Revision E Plan ref/date:

Prepared by: **DKO**



Ceiling penetrations

Sealed: Unsealed: 0

TOTAL:** 2

**NOTE: This total is the maximum number of ceiling (see following pages for details) penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616397-01** Certificate Date: **24 Feb 2020**





Building features

Window type	and performand	e value				
Window ID	Window type				U-value	SHGC
ALM-002-03 A	ALM-002-03 A A	Aluminium B SG	High Solar Gain I	Low-E	5.4	0.58
Window sche	dule					
Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	1200	W	Awning
Kitchen/Living	ALM-002-03 A	n/a	1800	3300	W	Awning

		e and performance				
ID	Window type				U-value	SHGC
None Present						
Roof window	and skylight sch	edule				
Location	ID	Roof	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser

ID	Wall type		Insulation		Wa	II wrap or fo
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	3445	2790	SW	No	1950
Kitchen/Living	EW-1	1882	2790	S	No	2247
Kitchen/Living	EW-1	1956	2790	W	No	0
Kitchen/Living	EW-1	3824	2790	W	No	0

Internal wall type				
Wall type	Area (m²)	Insulation	Wall wrap or foil	
IW-1 - Shaft liner party wall with plaster	54.0	Bulk Insulation both sides of shaft liner R1.5	No	
IW-2 - Cavity wall, direct fix plasterboard, single gap	26.0	No insulation	No	

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	13.2	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below	4.3	None	No Insulation	Ceramic Tiles

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616397-01** Certificate Date: **24 Feb 2020**

2020 ★ Star rating:



Building features continued

Kitchen/Living Concrete Slab, Unit Below 35.4 None No Insulation Cork Tiles or Parquetry 8mm		250mm				8mm
	Kitchen/Living		35.4	None	No Insulation	

Location	Construction	Added insulation	Roof space above
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling peneti	rations			
Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616371-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7.2



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 405, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-001-03 A Aluminium A SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 69.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 74.0


Annual thermal performance loads (MJ/m²)

Heating: **34.7** Cooling: **29.0** TOTAL: **63.7**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3

Unsealed: 0
TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616371-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-001-03 A	ALM-001-03 A Aluminium A SG High Solar Gain Low-E	5.4	0.49

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-001-03 A	n/a	2700	2400	W	No Shading
Bedroom 1	ALM-001-03 A	n/a	1800	2000	W	Awning
Kitchen/Living	ALM-001-03 A	n/a	1800	3000	W	Awning
Kitchen/Living	ALM-001-03 A	n/a	2700	2700	N	No Shading

ID	Window type				U-value	SHGC
None Present						
Roof window	v and skylight scl	hedule				
Location	ID	Roof window/skylight	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser

ID	Wall type		Insulation	Insulation W			
EW-1	Brick Veneer		Bulk Insulation	Bulk Insulation R1.5		No	
External wall	schedule						
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 2	EW-1	3010	2790	W	No	3121	
Bedroom 1	EW-1	3005	2790	W	No	0	
Kitchen/Living	EW-1	4031	2790	W	No	0	
Kitchen/Living	EW-1	3157	2790	N	No	4887	

Internal wall type					
Wall type	Area (m²)	Insulation	Wall wrap or foil		
IW-1 - Shaft liner party wall with plaster	67.0	Bulk Insulation both sides of shaft liner R1.5	No		
IW-2 - Cavity wall, direct fix plasterboard, single gap	55.0	No insulation	No		

Floors						
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering	
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm	

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616371-01 Certificate Date: 24 Feb 2020 ★ Star rating:



7.2

Building features continued Bedroom 2 10.7 Concrete Slab, Unit Below None No Insulation Carpet+Rubber 250mm Underlay 18mm Bath Concrete Slab, Unit Below 4.9 No Insulation **Ceramic Tiles** None 250mm 8mm Bedroom 1 Concrete Slab, Unit Below 15.3 None No Insulation Carpet+Rubber Underlay 18mm 250mm Concrete Slab, Unit Below Cork Tiles or Kitchen/Living 37.4 None No Insulation 250mm Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations				
Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		-

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616348-01 Certificate Date: 24 Feb 2020 ★ Star rating: 6.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: **BERS Pro v4.4.0.0 (3.21)**

AAO: BDAV

Overview

Dwelling details

Street: Unit 406, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS climate zone: 28

Lot/DP Climate zone. 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 73.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 78.0

Annual thermal performance loads (MJ/m²)

Heating: 25.8 Cooling: 54.1 TOTAL: 79.9

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**

6.4 The more stars the more energy efficient NATIONWIDE HOUSE ENERGY RATING SCHEME Predicted annual energy load for heating and cooling based on standard occupancy assumptions 79.9 MJ/m² For more information on your dwelling's rating see: www.nathers.gov.au

Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:** 3

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616348-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features

Window type and performance value					
Window ID	Window type	U-value	SHGC		
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58		

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	2100	W	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	N	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	Awning
Bedroom 2	ALM-002-03 A	n/a	2700	2400	W	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	3600	W	No Shading

ID	Window	type			U-value	SHGC
None Presen	it					
Roof windo	w and skyligh	nt schedule				
Location	ID	Roof	Area (m²)	Orientation	Outdoor shade	Indoor

ID	Wall type		Insulation	Insulation W		
EW-1	Brick Veneer	Bulk Insulation R1.5		No		
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	3081	2790	W	No	35
Bedroom 1	EW-1	5447	2790	N	No	35
Bedroom 1	EW-1	1092	2790	S	No	8596
Ens	EW-1	2220	2790	N	No	35
Bedroom 2	EW-1	3005	2790	W	No	2975
Bath	EW-1	917	2790	N	No	0
Bath	EW-1	743	2790	E	No	0
Bath	EW-1	618	2790	NE	No	0
Kitchen/Living	EW-1	1835	2790	S	No	4405
Kitchen/Living	EW-1	4102	2790	W	No	1134

Internal wall type					
Wall type	Area (m²)	Insulation	Wall wrap or foil		
IW-1 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No		
IW-2 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616348-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	16.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bedroom 2	Concrete Slab, Unit Below 250mm	10.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	4.5	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	40.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations						
Location	Number	Туре	Diameter (mm)	Sealed/unsealed		
Ens	1	Exhaust Fans	300	Sealed		
Bath	1	Exhaust Fans	300	Sealed		
Kitchen/Living	1	Exhaust Fans	300	Sealed		

Location Number Diameter (mm) None Present	Ceiling fans			
None Present	Location	Number	Diameter (mm)	
	None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616314-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7.0



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 407, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 74.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 79.0


Annual thermal performance loads (MJ/m²)

Heating: 20.5
Cooling: 45.4
TOTAL: 65.9

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616314-01 Certificate Date: 24 Feb 2020

★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2400	E	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	2400	Е	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	3900	Е	No Shading

Roof window	w and skylight	type and performanc	e value			
None Present	Window ty	ре			U-value	SHGC
Roof window	w and skylight	schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present						

ID	Wall type		Insulation		Wa	II wrap or fo
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall s	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	3043	2790	E	No	3173
Bedroom 1	EW-1	1129	2790	S	No	11336
Bedroom 1	EW-1	2296	2790	N	No	0
Bedroom 1	EW-1	3250	2790	N	No	25
Bedroom 1	EW-1	2512	2790	E	No	71
Ens	EW-1	2257	2790	N	No	0
Bath	EW-1	1315	2790	NW	No	25
Bath	EW-1	846	2790	N	No	35
Kitchen/Living	EW-1	4111	2790	Е	No	1207
Kitchen/Living	EW-1	1980	2790	S	No	6947

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616314-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.5	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 1	Concrete Slab, Unit Below 250mm	15.8	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.6	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	41.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling peneti	ations			
Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present	1		

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616298-02 Certificate Date: 24 Feb 2020 ★ Star rating: 7.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 408, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 73.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 78.0


Annual thermal performance loads (MJ/m²)

Heating: 18.0 Cooling: 40.3 TOTAL: 58.3

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

Unsealed: TOTAL:** **NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Document Set ID: 9129545 Version: 1, Version Date: 08/05/2020

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616298-02** Certificate Date: 24 Feb 2020 ★ Star rating:



Building features

Window type	and performance value		
Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58
Window sched	dule		

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	850	E	Awning
Bedroom 1	ALM-002-03 A	n/a	1800	1550	E	Awning
Bedroom 2	ALM-002-03 A	n/a	2700	2400	Е	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	3000	E	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	2700	N	No Shading

ID	Window	type			U-value	SHGC
None Presen	t					
nooi wiiido	w and skyligh	it schedule				
Location	ID	Roof window/skylight	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser

ID	Wall type		Insulation		Wa	II wrap or foi		
EW-1	Brick Veneer		Bulk Insulation	Bulk Insulation R1.5		No		
External wall schedule								
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)		
Bedroom 1	EW-1	950	2790	E	No	71		
Bedroom 1	EW-1	1773	2790	E	No	56		
Bedroom 1	EW-1	600	2790	NE	No	25		
Bedroom 2	EW-1	3073	2790	E	No	3042		
Kitchen/Living	EW-1	4172	2790	E	No	35		
Kitchen/Living	EW-1	3015	2790	N	No	5508		

Internal wall type						
Wall type	Area (m²)	Insulation	Wall wrap or foil			
IW-1 - Shaft liner party wall with plaster	71.0	Bulk Insulation both sides of shaft liner R1.5	No			
IW-2 - Cavity wall, direct fix plasterboard, single gap	57.0	No insulation	No			

Floors

Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616298-02 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Ens	Concrete Slab, Unit Below 250mm	5.9	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	5.1	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	38.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616744-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 501, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

Lot/DP

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 74.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 79.0


Annual thermal performance loads (MJ/m²)

Heating: 25.1 Cooling: 31.7 TOTAL: 56.9

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3

Unsealed: 0
TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616744-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features

Window type and performance value					
Window ID	Window type	U-value	SHGC		
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58		

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	900	NE	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	SE	Awning
Bedroom 1	ALM-002-03 A	n/a	2700	1800	NW	No Shading
Bedroom 2	ALM-002-03 A	n/a	1800	900	SE	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	3600	NE	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	1500	NE	No Shading
Ens	ALM-002-03 A	n/a	1800	900	SE	Awning

ID	Window	type		U-value	SHGC
None Presen	t				
Roof windo	w and skyligh	nt schedule			
TIOOT WIIIGO	w and oxyngi				

ID	Wall type		Insulation		Wa	II wrap or foi	
EW-1	Brick Veneer		Bulk Insulation	R1.5 No		0	
External wall	schedule						
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 1	EW-1	2800	2790	NE	No	0	
Bedroom 1	EW-1	335	2790	Е	No	0	
Bedroom 1	EW-1	320	2790	E	No	0	
Bedroom 1	EW-1	3245	2790	SE	No	0	
Bedroom 1	EW-1	1850	2790	NW	No	7050	
Bedroom 2	EW-1	2795	2790	SE	No	0	
Bedroom 2	EW-1	762	2790	SW	No	56	
Bedroom 2	EW-1	610	2790	S	No	25	
Kitchen/Living	EW-1	5945	2790	NE	No	1850	
Kitchen/Living	EW-1	1900	2790	NW	No	1125	
Ens	EW-1	2840	2790	SE	No	0	

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
	59.0	No insulation	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616744-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7



Building features continued

IW-1 - Cavity wall, direct fix plasterboard, single gap

IW-2 - Shaft liner party wall with 41.0 Bulk Insulation both sides of shaft liner R1.5 No

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	5.0	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	13.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.7	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	43.1	None	No Insulation	Cork Tiles or Parquetry 8mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed
Ens	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616702-01 Certificate Date: 24 Feb 2020 ★ Star rating: 5.9



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 502, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 71.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 76.0


Annual thermal performance loads (MJ/m²)

Heating: 57.9
Cooling: 32.0
TOTAL: 89.8

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616702-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

window type a	and performance value		
Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2700	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	3700	SW	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	SE	Awning
Bedroom 1	ALM-002-03 A	n/a	1800	2350	SW	Awning
Ens	ALM-002-03 A	n/a	1800	900	SE	Awning

ID	Window	type			U-value	SHGC
None Presen	it					
Roof windo	w and skyligh	nt schedule				
Location	ID	Roof	Area (m²)	Orientation	Outdoor shade	Indoor

ID	Wall type		Insulation		W	all wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	N	0
EW-2	Brick Veneer		Foil, Anti-glare	e one side, Refle	ctive other Y	es
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	2995	2790	SW	No	2925
Kitchen/Living	EW-1	3995	2790	SW	No	1175
Kitchen/Living	EW-1	1750	2790	NW	No	4725
Bedroom 1	EW-1	1150	2790	NW	No	8675
Bedroom 1	EW-1	4845	2790	SE	No	0
Bedroom 1	EW-1	707	2790	S	No	0
Bedroom 1	EW-1	2600	2790	SW	No	0
Ens	EW-1	2240	2790	SE	No	0
Bath	EW-1	1242	2790	Е	No	0
Bath	EW-1	895	2790	SE	No	0

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Cavity wall, direct fix plasterboard, single gap	61.0	No insulation	No
IW-2 - Shaft liner party wall with	43.0	Bulk Insulation both sides of shaft liner R1.5	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616702-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features continued

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.4	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	39.5	None	No Insulation	Cork Tiles or Parquetry 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 2	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Kitchen/Living	1	Exhaust Fans	300	Sealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type		
Construction	Added insulation	Roof colour
None Present		-

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: **0004616678-01** Certificate Date: 24 Feb 2020 ★ Star rating: 5.4



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: 07 3069 5757

Declaration None

of interest:

BERS Pro v4.4.0.0 (3.21) Software:

BDAV AAO:

Overview

Dwelling details

Unit 503, Lot 3008 Lord Sheffield Circuit Street:

Suburb: Penrith

Postcode: State: **NSW** 2750 NCC Class: 2 **New Dwelling** Type:

NatHERS

climate zone: 28 Lot/DP

number: 3008/-Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

> No ceiling insulation No floor insulation

ALM-002-03 A Aluminium B SG High Glazing:

Solar Gain Low-E

Net floor area (m²)

Conditioned: 44.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 48.0


Annual thermal performance loads (MJ/m²)

Heating: 51.6 Cooling: 51.1 TOTAL: 102.7

Plan documents

11749, Revision E Plan ref/date:

Prepared by: **DKO**



Ceiling penetrations

Sealed: Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling (see following pages for details) penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

2

Window selection default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616678-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	2100	SW	Awning
Kitchen/Living	ALM-002-03 A	n/a	1800	900	SW	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	2400	NW	No Shading

Roof window and skylight type and performance value							
None Present	Window	type			U-value	SHGC	
Roof window and skylight schedule							
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser	
None Present							

ID	Wall type		Insulation		Wa	Wall wrap or foil	
EW-1	Brick Veneer		Bulk Insulation R1.5		No	No	
External wall	schedule						
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 1	EW-1	2995	2790	SW	No	2600	
Kitchen/Living	EW-1	2850	2790	SE	No	3025	
Kitchen/Living	EW-1	3700	2790	SW	No	0	
Kitchen/Living	EW-1	2600	2790	NW	No	4450	

Internal wall type					
Wall type	Area (m²)	Insulation	Wall wrap or foil		
IW-1 - Shaft liner party wall with plaster	51.0	Bulk Insulation both sides of shaft liner R1.5	No		
IW-2 - Cavity wall, direct fix plasterboard, single gap	25.0	No insulation	No		

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	4.2	None	No Insulation	Ceramic Tiles 8mm

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616678-01 Certificate Date: 24 Feb 2020





5.4

Building features continued Bedroom 1 Concrete Slab, Unit Below 12.1 None No Insulation Carpet+Rubber Underlay 18mm 250mm Kitchen/Living Concrete Slab, Unit Below 31.7 None No Insulation Cork Tiles or 250mm Parquetry 8mm

Ceiling type			
Location	Construction	Added insulation	Roof space above
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type	
Construction	Added Roof colour insulation
None Present	

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616645-01 Certificate Date: 24 Feb 2020 ★ Star rating: 6.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: **BERS Pro v4.4.0.0 (3.21)**

AAO: BDAV

Overview

Dwelling details

Street: Unit 504, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 49.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 53.0


Annual thermal performance loads (MJ/m²)

Heating: 41.0 Cooling: 38.7 TOTAL: 79.7

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 2
Unsealed: 0

Unsealed: 0
TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616645-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window type	and performance value		
Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	1200	W	Awning
Kitchen/Living	ALM-002-03 A	n/a	1800	3300	W	Awning

ID	Window type				U-value	SHGC
None Present	,,					
Roof window	and skylight sch	edule				
Location	ID	Roof	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser

ID	Wall type		Insulation		Wa	II wrap or foi	
EW-1	Brick Veneer	Bulk Insulation R1.5		n R1.5	No		
External wall	schedule						
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 1	EW-1	3445	2790	SW	No	1950	
Kitchen/Living	EW-1	1882	2790	S	No	2247	
Kitchen/Living	EW-1	1956	2790	W	No	0	
Kitchen/Living	EW-1	3824	2790	W	No	0	

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	54.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	26.0	No insulation	No

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	13.2	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below	4.3	None	No Insulation	Ceramic Tiles

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616645-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features continued

	250mm				8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	35.4	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Construction	Added Roof colou insulation
None Present	

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616611-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7.2



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 505, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS climate zone: 28

Lot/DP Climate zone. 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-001-03 A Aluminium A SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 69.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 74.0


Annual thermal performance loads (MJ/m²)

Heating: **35.1**Cooling: **28.7**TOTAL: **63.7**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3 Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616611-01 Certificate Date: 24 Feb 2020

★ Star rating:



Building features

Window type and	I performance value
-----------------	---------------------

Window ID	Window type	U-value	SHGC
ALM-001-03 A	ALM-001-03 A Aluminium A SG High Solar Gain Low-E	5.4	0.49

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-001-03 A	n/a	2700	2400	W	No Shading
Bedroom 1	ALM-001-03 A	n/a	1800	2000	W	Awning
Kitchen/Living	ALM-001-03 A	n/a	1800	3000	W	Awning
Kitchen/Living	ALM-001-03 A	n/a	2700	2700	N	No Shading

Roof window	v and skylight typ	e and performanc	e value			
None Present	Window type				U-value	SHGC
Roof window	v and skylight scl	nedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present						

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No	<u> </u>
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	3010	2790	W	No	3121
Bedroom 1	EW-1	3005	2790	W	No	0
Kitchen/Living	EW-1	4031	2790	W	No	0
Kitchen/Living	EW-1	3157	2790	N	No	4887

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	67.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	55.0	No insulation	No

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616611-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Bedroom 2	Concrete Slab, Unit Below 250mm	10.7	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	4.9	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	15.3	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	37.4	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations				
Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: **0004616363-01** Certificate Date: 24 Feb 2020 ★ Star rating: 6.4



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: 07 3069 5757

Declaration None

of interest:

BERS Pro v4.4.0.0 (3.21) Software:

BDAV AAO:

Overview

Dwelling details

Unit 506, Lot 3008 Lord Sheffield Circuit Street:

Suburb: Penrith

Postcode: State: **NSW** 2750 NCC Class: 2 **New Dwelling** Type:

NatHERS

climate zone: 28 Lot/DP

number: 3008/-Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

> No ceiling insulation No floor insulation

ALM-002-03 A Aluminium B SG High Glazing:

Solar Gain Low-E

Net floor area (m²)

Conditioned: 73.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 78.0


Annual thermal performance loads (MJ/m²)

Heating: 26.3 Cooling: 52.4 TOTAL: 78.7

Plan documents

11749, Revision E Plan ref/date:

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: Unsealed:

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

0

3

Window selection default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616363-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features

Window type an	d performance value
----------------	---------------------

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	2100	W	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	N	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	Awning
Bedroom 2	ALM-002-03 A	n/a	2700	2400	W	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	3600	W	No Shading

Roof window	w and skylig	ht type and performanc	e value			
ID	Window	type			U-value	SHGC
None Present	t					-
Roof window	w and skylig	ht schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present	t	-		-	-	

ID	Wall type		Insulation		Wa	III wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	3081	2790	W	No	35
Bedroom 1	EW-1	5447	2790	N	No	35
Bedroom 1	EW-1	1092	2790	S	No	8596
Ens	EW-1	2220	2790	N	No	35
Bedroom 2	EW-1	3005	2790	W	No	2975
Bath	EW-1	917	2790	N	No	0
Bath	EW-1	743	2790	Е	No	0
Bath	EW-1	618	2790	NE	No	0
Kitchen/Living	EW-1	1835	2790	S	No	4405
Kitchen/Living	EW-1	4102	2790	W	No	1134

Internal wall type				
Wall type	Area (m²)	Insulation	Wall wrap or foil	
IW-1 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No	
IW-2 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No	

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616363-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	16.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bedroom 2	Concrete Slab, Unit Below 250mm	10.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	4.5	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	40.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations				
Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		-

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: **0004616587-01** Certificate Date: 24 Feb 2020 ★ Star rating: 6.9



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: 07 3069 5757

Declaration None

of interest:

BERS Pro v4.4.0.0 (3.21) Software:

BDAV AAO:

Overview

Dwelling details

Unit 507, Lot 3008 Lord Sheffield Circuit Street:

Suburb: Penrith

Postcode: State: **NSW** 2750 NCC Class: 2 **New Dwelling** Type:

NatHERS

climate zone: 28 Lot/DP

number: 3008/-Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

> No ceiling insulation No floor insulation

ALM-002-03 A Aluminium B SG High Glazing:

Solar Gain Low-E

Net floor area (m²)

Conditioned: 74.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 79.0


Annual thermal performance loads (MJ/m²)

Heating: 20.9 Cooling: 45.2 TOTAL: 66.2

Plan documents

11749, Revision E Plan ref/date:

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: Unsealed:

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

0

3

Window selection default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Version: 1, Version Date: 08/05/2020

Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616587-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window t	type a	and _I	performance	value
----------	--------	------------------	-------------	-------

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2400	E	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	2400	Е	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	3900	Е	No Shading

Roof window	w and skyligh	t type and performanc	e value			
None Present	Window	type			U-value	SHGC
Roof window	w and skyligh	t schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present						

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	3043	2790	E	No	3173
Bedroom 1	EW-1	1129	2790	S	No	11336
Bedroom 1	EW-1	2296	2790	N	No	0
Bedroom 1	EW-1	3250	2790	N	No	25
Bedroom 1	EW-1	2512	2790	Е	No	71
Ens	EW-1	2257	2790	N	No	0
Bath	EW-1	1315	2790	NW	No	25
Bath	EW-1	846	2790	N	No	35
Kitchen/Living	EW-1	4111	2790	Е	No	1207
Kitchen/Living	EW-1	1980	2790	S	No	6947

Internal wall type				
Wall type	Area (m²)	Insulation	Wall wrap or foil	
IW-1 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No	
IW-2 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No	

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616587-01** Certificate Date: **24**

24 Feb 2020 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.5	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 1	Concrete Slab, Unit Below 250mm	15.8	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.6	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	41.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations				
Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: **0004616561-02** Certificate Date: 24 Feb 2020 ★ Star rating: 7.4



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: 07 3069 5757

Declaration None

of interest:

BERS Pro v4.4.0.0 (3.21) Software:

BDAV AAO:

Overview

Dwelling details

Unit 508, Lot 3008 Lord Sheffield Circuit Street:

Suburb: Penrith

Postcode: State: **NSW** 2750 NCC Class: 2 **New Dwelling** Type:

NatHERS

climate zone: 28 Lot/DP

number: 3008/-Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

> No ceiling insulation No floor insulation

ALM-002-03 A Aluminium B SG High Glazing:

Solar Gain Low-E

Net floor area (m²)

Conditioned: 73.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 78.0


Annual thermal performance loads (MJ/m²)

Heating: 18.4 Cooling: 40.2 TOTAL: 58.6

Plan documents

11749, Revision E Plan ref/date:

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: Unsealed:

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

0

3

Window selection default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616561-02 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	850	E	Awning
Bedroom 1	ALM-002-03 A	n/a	1800	1550	E	Awning
Bedroom 2	ALM-002-03 A	n/a	2700	2400	E	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	3000	E	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	2700	N	No Shading

ID	Window	type		U-value	SHGC
None Present	t				
Root windo	w and skyligh		Area (m²)	Outdoor shade	
Location	ID	Roof			

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation R1.5		No	
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	950	2790	E	No	71
Bedroom 1	EW-1	1773	2790	E	No	56
Bedroom 1	EW-1	600	2790	NE	No	25
Bedroom 2	EW-1	3073	2790	E	No	3042
Kitchen/Living	EW-1	4172	2790	E	No	35
Kitchen/Living	EW-1	3015	2790	N	No	5508

Internal wall type				
Wall type	Area (m²)	Insulation	Wall wrap or foil	
IW-1 - Shaft liner party wall with plaster	71.0	Bulk Insulation both sides of shaft liner R1.5	No	
IW-2 - Cavity wall, direct fix plasterboard, single gap	57.0	No insulation	No	

Floors

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616561-02 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Ens	Concrete Slab, Unit Below 250mm	5.9	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	5.1	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	38.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616520-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 601, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 74.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 79.0


Annual thermal performance loads (MJ/m²)

Heating: 25.4
Cooling: 31.6
TOTAL: 57.0

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616520-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

window type a	and performance value		
Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	900	NE	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	SE	Awning
Bedroom 1	ALM-002-03 A	n/a	2700	1800	NW	No Shading
Bedroom 2	ALM-002-03 A	n/a	1800	900	SE	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	3600	NE	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	1500	NE	No Shading
Ens	ALM-002-03 A	n/a	1800	900	SE	Awning

ID	Window	type		U-value	SHGC
None Presen	t				
Roof windo	w and skyligh	nt schedule			

ID	Wall type		Insulation	Insulation Wa		all wrap or foil	
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No		
External wall	schedule						
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 1	EW-1	2800	2790	NE	No	0	
Bedroom 1	EW-1	335	2790	Е	No	0	
Bedroom 1	EW-1	320	2790	E	No	0	
Bedroom 1	EW-1	3245	2790	SE	No	0	
Bedroom 1	EW-1	1850	2790	NW	No	7050	
Bedroom 2	EW-1	2795	2790	SE	No	0	
Bedroom 2	EW-1	762	2790	SW	No	56	
Bedroom 2	EW-1	610	2790	S	No	25	
Kitchen/Living	EW-1	5945	2790	NE	No	1850	
Kitchen/Living	EW-1	1900	2790	NW	No	1125	
Ens	EW-1	2840	2790	SE	No	0	

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
	59.0	No insulation	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616520-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

IW-1 - Cavity wall, direct fix plasterboard, single gap

IW-2 - Shaft liner party wall with 41.0 Bulk Insulation both sides of shaft liner R1.5 No

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	5.0	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	13.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.7	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	43.1	None	No Insulation	Cork Tiles or Parquetry 8mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed
Ens	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: **0004616496-01** Certificate Date: 24 Feb 2020 ★ Star rating: 5.9



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: 07 3069 5757

Declaration None

of interest:

BERS Pro v4.4.0.0 (3.21) Software:

BDAV AAO:

Overview

Dwelling details

Unit 602, Lot 3008 Lord Sheffield Circuit Street:

Suburb: Penrith

Postcode: State: **NSW** 2750 NCC Class: 2 **New Dwelling** Type:

NatHERS

climate zone: 28 Lot/DP

number: 3008/-Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

> No ceiling insulation No floor insulation

ALM-002-03 A Aluminium B SG High Glazing:

Solar Gain Low-E

Net floor area (m²)

Conditioned: 71.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 76.0

Annual thermal performance loads (MJ/m²)

Heating: 58.3 Cooling: 31.8 TOTAL: 90.1

Plan documents

11749, Revision E Plan ref/date:

Prepared by: **DKO**

the more energy efficient NATIONWIDE Predicted annual energy load for heating and cooling based on standard occupancy assumptions MJ/m² For more information on your dwelling's rating see: www.nathers.gov.au

Ceiling penetrations

(see following pages for details)

Sealed: Unsealed:

TOTAL:** 3 **NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

0

Window selection default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Version: 1, Version Date: 08/05/2020

Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616496-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window ty	pe and p	performance	value
-----------	----------	-------------	-------

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2700	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	3700	SW	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	SE	Awning
Bedroom 1	ALM-002-03 A	n/a	1800	2350	SW	Awning
Ens	ALM-002-03 A	n/a	1800	900	SE	Awning

Roof windo	w and skylig	ht type and performanc	e value			
ID	Window	v type			U-value	SHGC
None Presen	nt					-
Roof windo	w and skylig	ht schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser

External wall type					
ID	Wall type	Insulation	Wall wrap or foil		
EW-1	Brick Veneer	Bulk Insulation R1.5	No		
EW-2	Brick Veneer	Foil, Anti-glare one side, Reflective other	Yes		

External wall schedule

None Present

Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	2995	2790	SW	No	2925
Kitchen/Living	EW-1	3995	2790	SW	No	1175
Kitchen/Living	EW-1	1750	2790	NW	No	4725
Bedroom 1	EW-1	1150	2790	NW	No	8675
Bedroom 1	EW-1	4845	2790	SE	No	0
Bedroom 1	EW-1	707	2790	S	No	0
Bedroom 1	EW-1	2600	2790	SW	No	0
Ens	EW-1	2240	2790	SE	No	0
Bath	EW-1	1242	2790	E	No	0
Bath	EW-1	895	2790	SE	No	0

Internal wall type						
Wall type	Area (m²)	Insulation	Wall wrap or foil			
IW-1 - Cavity wall, direct fix plasterboard, single gap	61.0	No insulation	No			
IW-2 - Shaft liner party wall with	43.0	Bulk Insulation both sides of shaft liner R1.5	No			

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616496-01 Certificate Date: 24 Feb

24 Feb 2020 ★ Star rating:



Building features continued

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.4	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	39.5	None	No Insulation	Cork Tiles or Parquetry 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 2	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Kitchen/Living	1	Exhaust Fans	300	Sealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed

Location Number Diameter (mm)	
None Present	

Roof type		
Construction	Added insulation	Roof colour
None Present		-

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616462-02 Certificate Date: 24 Feb 2020 ★ Star rating: 5.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: **BERS Pro v4.4.0.0 (3.21)**

AAO: BDAV

Overview

Dwelling details

Street: Unit 603, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 44.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 48.0


Annual thermal performance loads (MJ/m²)

Heating: **52.0** Cooling: **50.7** TOTAL: **102.8**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 2

Unsealed: 0
TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616462-02** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	2100	SW	Awning
Kitchen/Living	ALM-002-03 A	n/a	1800	900	SW	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	2400	NW	No Shading

Roof window and skylight type and performance value						
None Present	Window	type			U-value	SHGC
Roof window	w and skyligh	t schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present						

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation R1.5		No	
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	2995	2790	SW	No	2600
Kitchen/Living	EW-1	2850	2790	SE	No	3025
Kitchen/Living	EW-1	3700	2790	SW	No	0
Kitchen/Living	EW-1	2600	2790	NW	No	4450

Internal wall type					
Wall type	Area (m²)	Insulation	Wall wrap or foil		
IW-1 - Shaft liner party wall with plaster	51.0	Bulk Insulation both sides of shaft liner R1.5	No		
IW-2 - Cavity wall, direct fix plasterboard, single gap	25.0	No insulation	No		

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	4.2	None	No Insulation	Ceramic Tiles 8mm

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

250mm

Certificate number: 0004616462-02 Certificate Date: 24 Feb 2020 ★ Star rating:



5.4

Parquetry 8mm

Bedroom 1 Concrete Slab, Unit Below 250mm 12.1 None No Insulation Carpet+Rubber Underlay 18mm Kitchen/Living Concrete Slab, Unit Below 31.7 None No Insulation Cork Tiles or

Ceiling type					
Location	Construction	Added insulation	Roof space above		
Bath	Concrete, Plasterboard	No insulation	No		
Bedroom 1	Concrete, Plasterboard	No insulation	No		
Kitchen/Living	Concrete, Plasterboard	No insulation	No		

Ceiling penetrations					
Location	Number	Туре	Diameter (mm)	Sealed/unsealed	
Bath	1	Exhaust Fans	300	Sealed	
Kitchen/Living	1	Exhaust Fans	300	Sealed	

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type	
Construction	Added Roof colour insulation
None Present	

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 604, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 49.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 53.0


Annual thermal performance loads (MJ/m²)

Heating: 41.4 Cooling: 38.6 TOTAL: 80.0

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 2
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

2

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616439-02** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window type	and performanc	e value				
Window ID	Window type				U-value	SHGC
ALM-002-03 A	ALM-002-03 A A	Aluminium B SG	High Solar Gain I	Low-E	5.4	0.58
Window sche	dule					
Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	1200	W	Awning
Kitchen/Living	ALM-002-03 A	n/a	1800	3300	W	Awning

Roof windo	w and skylight typ	e and performanc	e value			
ID	Window type				U-value	SHGC
None Present	t					
Roof windo	w and skylight sch	nedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present	t					

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	3445	2790	SW	No	1950
Kitchen/Living	EW-1	1882	2790	S	No	2247
Kitchen/Living	EW-1	1956	2790	W	No	0
Kitchen/Living	EW-1	3824	2790	W	No	0

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	54.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	26.0	No insulation	No

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	13.2	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below	4.3	None	No Insulation	Ceramic Tiles

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616439-02** Certificate Date: **24**

24 Feb 2020 ★ Star rating:



Building features continued

Kitchen/Living Concrete Slab, Unit Below 35.4 None No Insulation Cork Tiles or Parquetry 8mm		250mm				8mm
	Kitchen/Living		35.4	None	No Insulation	

Ceiling type			
Location	Construction	Added insulation	Roof space above
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616405-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7.1



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 605, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-001-03 A Aluminium A SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 69.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 74.0


Annual thermal performance loads (MJ/m²)

Heating: **35.4**Cooling: **28.4**TOTAL: **63.9**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

Unsealed: 0
TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616405-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window	type and	performance value
--------	----------	-------------------

Window ID	Window type	U-value	SHGC
ALM-001-03 A	ALM-001-03 A Aluminium A SG High Solar Gain Low-E	5.4	0.49

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-001-03 A	n/a	2700	2400	W	No Shading
Bedroom 1	ALM-001-03 A	n/a	1800	2000	W	Awning
Kitchen/Living	ALM-001-03 A	n/a	1800	3000	W	Awning
Kitchen/Living	ALM-001-03 A	n/a	2700	2700	N	No Shading

Roof window	w and skylight	type and performanc	e value			
None Present	Window ty	ре			U-value	SHGC
Roof window	w and skylight	schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present						

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No	<u> </u>
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	3010	2790	W	No	3121
Bedroom 1	EW-1	3005	2790	W	No	0
Kitchen/Living	EW-1	4031	2790	W	No	0
Kitchen/Living	EW-1	3157	2790	N	No	4887

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	67.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	55.0	No insulation	No

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

24 Feb 2020 Certificate number: **0004616405-01** Certificate Date: ★ Star rating:



Building featur	es continued				
Bedroom 2	Concrete Slab, Unit Below 250mm	10.7	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	4.9	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	15.3	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	37.4	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations				
Number	Туре	Diameter (mm)	Sealed/unsealed	
1	Exhaust Fans	300	Sealed	
1	Exhaust Fans	300	Sealed	
1	Exhaust Fans	300	Sealed	
		NumberType1Exhaust Fans1Exhaust Fans	NumberTypeDiameter (mm)1Exhaust Fans3001Exhaust Fans300	

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		-

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616330-01 Certificate Date: 24 Feb 2020 ★ Star rating: 6.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: **BERS Pro v4.4.0.0 (3.21)**

AAO: BDAV

Overview

Dwelling details

Street: Unit 606, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 73.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 78.0


Annual thermal performance loads (MJ/m²)

Heating: 26.5
Cooling: 51.9
TOTAL: 78.3

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Document Set ID: 9129545 Version: 1, Version Date: 08/05/2020

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616330-01 Certificate Date: 24 Feb 2020 ★

★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	2100	W	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	N	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	Awning
Bedroom 2	ALM-002-03 A	n/a	2700	2400	W	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	3600	W	No Shading

ID	Window	type			U-value	SHGC
None Presen	it					
Roof windo	w and skyligh	nt schedule				
Location	ID	Roof	Area (m²)	Orientation	Outdoor shade	Indoor

ID	Wall type		Insulation		Wa	II wrap or
EW-1	Brick Veneer	Bulk Insulation R1.5		No)	
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	3081	2790	W	No	35
Bedroom 1	EW-1	5447	2790	N	No	35
Bedroom 1	EW-1	1092	2790	S	No	8596
Ens	EW-1	2220	2790	N	No	35
Bedroom 2	EW-1	3005	2790	W	No	2975
Bath	EW-1	917	2790	N	No	0
Bath	EW-1	743	2790	Е	No	0
Bath	EW-1	618	2790	NE	No	0
Kitchen/Living	EW-1	1835	2790	S	No	4405
Kitchen/Living	EW-1	4102	2790	W	No	1134

Internal wall type					
Wall type	Area (m²)	Insulation	Wall wrap or foil		
IW-1 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No		
IW-2 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616330-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	16.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bedroom 2	Concrete Slab, Unit Below 250mm	10.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	4.5	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	40.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

ations			
Number	Туре	Diameter (mm)	Sealed/unsealed
1	Exhaust Fans	300	Sealed
1	Exhaust Fans	300	Sealed
1	Exhaust Fans	300	Sealed
		NumberType1Exhaust Fans1Exhaust Fans	NumberTypeDiameter (mm)1Exhaust Fans3001Exhaust Fans300

Location Number Diameter (mm) None Present	Ceiling fans			
None Present	Location	Number	Diameter (mm)	
	None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616306-01 Certificate Date: 24 Feb 2020 ★ Star rating: 6.9



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: **BERS Pro v4.4.0.0 (3.21)**

AAO: BDAV

Overview

Dwelling details

Street: Unit 607, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 74.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 79.0


Annual thermal performance loads (MJ/m²)

Heating: 21.3
Cooling: 45.0
TOTAL: 66.2

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the

**NOTE: This total is the

Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616306-01** Certificate Date: **24 Fe**

24 Feb 2020 ★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2400	E	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	2400	Е	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	3900	Е	No Shading

Roof window	w and skylight	type and performance	e value			
None Present	Window t	ype			U-value	SHGC
Roof window	w and skylight	schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present						

ID	Wall type		Insulation		Wall wrap or fo	
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	3043	2790	E	No	3173
Bedroom 1	EW-1	1129	2790	S	No	11336
Bedroom 1	EW-1	2296	2790	N	No	0
Bedroom 1	EW-1	3250	2790	N	No	25
Bedroom 1	EW-1	2512	2790	E	No	71
Ens	EW-1	2257	2790	N	No	0
Bath	EW-1	1315	2790	NW	No	25
Bath	EW-1	846	2790	N	No	35
Kitchen/Living	EW-1	4111	2790	Е	No	1207
Kitchen/Living	EW-1	1980	2790	S	No	6947

Internal wall type						
Wall type	Area (m²)	Insulation	Wall wrap or foil			
IW-1 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No			
IW-2 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No			

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616306-01** Certificate Date: **24 Feb 2020**

b 2020 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.5	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 1	Concrete Slab, Unit Below 250mm	15.8	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.6	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	41.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations					
Location	Number	Туре	Diameter (mm)	Sealed/unsealed	
Ens	1	Exhaust Fans	300	Sealed	
Bath	1	Exhaust Fans	300	Sealed	
Kitchen/Living	1	Exhaust Fans	300	Sealed	

Location Number Diameter (mm) None Present	Ceiling fans			
None Present	Location	Number	Diameter (mm)	
	None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616272-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 608, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 73.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 78.0


Annual thermal performance loads (MJ/m²)

Heating: 18.6 Cooling: 39.8 TOTAL: 58.5

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616272-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	850	E	Awning
Bedroom 1	ALM-002-03 A	n/a	1800	1550	E	Awning
Bedroom 2	ALM-002-03 A	n/a	2700	2400	E	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	3000	E	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	2700	N	No Shading

ID	Window type				U-value	SHGC
None Present						
Roof windov	v and skylight sch	edule				
Location	ID	Roof window/skylight	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser

ID	Wall type		Insulation		Wa	II wrap or fo
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall s	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	950	2790	E	No	71
Bedroom 1	EW-1	1773	2790	E	No	56
Bedroom 1	EW-1	600	2790	NE	No	25
Bedroom 2	EW-1	3073	2790	E	No	3042
Kitchen/Living	EW-1	4172	2790	E	No	35
Kitchen/Living	EW-1	3015	2790	N	No	5508

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	71.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	57.0	No insulation	No

Floors

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616272-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Ens	Concrete Slab, Unit Below 250mm	5.9	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	5.1	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	38.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Ceiling type			
Location	Construction	Added insulation	Roof space above
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616736-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: **BERS Pro v4.4.0.0 (3.21)**

AAO: BDAV

Overview

Dwelling details

Street: Unit 701, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 74.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 79.0


Annual thermal performance loads (MJ/m²)

Heating: 25.7 Cooling: 31.5 TOTAL: 57.2

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3 Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616736-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	900	NE	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	SE	Awning
Bedroom 1	ALM-002-03 A	n/a	2700	1800	NW	No Shading
Bedroom 2	ALM-002-03 A	n/a	1800	900	SE	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	3600	NE	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	1500	NE	No Shading
Ens	ALM-002-03 A	n/a	1800	900	SE	Awning

ID	Window	type		U-value	SHGC
None Presen	t				
Roof windo	w and skyligh	nt schedule			

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No	
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	2800	2790	NE	No	0
Bedroom 1	EW-1	335	2790	Е	No	0
Bedroom 1	EW-1	320	2790	E	No	0
Bedroom 1	EW-1	3245	2790	SE	No	0
Bedroom 1	EW-1	1850	2790	NW	No	7050
Bedroom 2	EW-1	2795	2790	SE	No	0
Bedroom 2	EW-1	762	2790	SW	No	56
Bedroom 2	EW-1	610	2790	S	No	25
Kitchen/Living	EW-1	5945	2790	NE	No	1850
Kitchen/Living	EW-1	1900	2790	NW	No	1125
Ens	EW-1	2840	2790	SE	No	0

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
	59.0	No insulation	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616736-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7



Building features continued

IW-1 - Cavity wall, direct fix plasterboard, single gap

IW-2 - Shaft liner party wall with 41.0 Bulk Insulation both sides of shaft liner R1.5 No

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	5.0	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	13.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.7	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	43.1	None	No Insulation	Cork Tiles or Parquetry 8mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed
Ens	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616710-01 Certificate Date: 24 Feb 2020 ★ Star rating: 5.9



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 702, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 71.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 76.0


Annual thermal performance loads (MJ/m²)

Heating: 58.7
Cooling: 31.8
TOTAL: 90.5

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3 Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616710-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

W	indo	w type	and performance value	

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2700	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	3700	SW	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	SE	Awning
Bedroom 1	ALM-002-03 A	n/a	1800	2350	SW	Awning
Ens	ALM-002-03 A	n/a	1800	900	SE	Awning

ID	Window	type		U-value	SHGC
None Presen	t				
Roof windo	w and skyligl	nt schedule			

ID	Wall type		Insulation		Wa	all wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No	0
EW-2	Brick Veneer		Foil, Anti-glare	e one side, Refle	ctive other Ye	es
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	2995	2790	SW	No	2925
Kitchen/Living	EW-1	3995	2790	SW	No	1175
Kitchen/Living	EW-1	1750	2790	NW	No	4725
Bedroom 1	EW-1	1150	2790	NW	No	8675
Bedroom 1	EW-1	4845	2790	SE	No	0
Bedroom 1	EW-1	707	2790	S	No	0
Bedroom 1	EW-1	2600	2790	SW	No	0
Ens	EW-1	2240	2790	SE	No	0
Bath	EW-1	1242	2790	E	No	0
Bath	EW-1	895	2790	SE	No	0

Internal wall type					
Wall type	Area (m²)	Insulation	Wall wrap or foil		
IW-1 - Cavity wall, direct fix plasterboard, single gap	61.0	No insulation	No		
IW-2 - Shaft liner party wall with	43.0	Bulk Insulation both sides of shaft liner R1.5	No		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616710-01** Certificate Date: **24 F**6

24 Feb 2020 ★ Star rating:



Building features continued

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.4	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	39.5	None	No Insulation	Cork Tiles or Parquetry 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 2	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Kitchen/Living	1	Exhaust Fans	300	Sealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type		
Construction	Added insulation	Roof colour
None Present		-

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 703, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 44.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 48.0


Annual thermal performance loads (MJ/m²)

Heating: **52.5**Cooling: **50.8**TOTAL: **103.2**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 2

Unsealed: 0
TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616686-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	2100	SW	Awning
Kitchen/Living	ALM-002-03 A	n/a	1800	900	SW	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	2400	NW	No Shading

Roof window	w and skylight	type and performance	e value			
None Present	Window t	ype			U-value	SHGC
Roof window	w and skylight	schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present						

ID	Wall type		Insulation	Insulation V			
EW-1	Brick Veneer		Bulk Insulation R1.5		No	No	
External wall	schedule						
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 1	EW-1	2995	2790	SW	No	2600	
Kitchen/Living	EW-1	2850	2790	SE	No	3025	
Kitchen/Living	EW-1	3700	2790	SW	No	0	
Kitchen/Living	EW-1	2600	2790	NW	No	4450	

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	51.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	25.0	No insulation	No

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	4.2	None	No Insulation	Ceramic Tiles 8mm

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

24 Feb 2020 Certificate number: **0004616686-01** Certificate Date: ★ Star rating:



Building featui	res continued				
Bedroom 1	Concrete Slab, Unit Below 250mm	12.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	31.7	None	No Insulation	Cork Tiles or Parquetry 8mm

Construction	Added insulation	Roof space above
Concrete, Plasterboard	No insulation	No
Concrete, Plasterboard	No insulation	No
Concrete, Plasterboard	No insulation	No
	Concrete, Plasterboard Concrete, Plasterboard	Concrete, Plasterboard No insulation Concrete, Plasterboard No insulation

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type		
Construction	Added Roof colou insulation	ır
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616652-01 Certificate Date: 24 Feb 2020 ★ Star rating: 6.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: **BERS Pro v4.4.0.0 (3.21)**

AAO: BDAV

Overview

Dwelling details

Street: Unit 704, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 49.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 53.0


Annual thermal performance loads (MJ/m²)

Heating: 41.8 Cooling: 38.4 TOTAL: 80.1

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 2

Unsealed: 0
TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616652-01** Certificate Date: **24 Feb 2020**





Building features

Window type	and performanc	e value				
Window ID	Window type				U-value	SHGC
ALM-002-03 A	ALM-002-03 A A	Numinium B SG	i High Solar Gain I	_ow-E	5.4	0.58
Window schedule						
Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	1200	W	Awning
Kitchen/Living	ALM-002-03 A	n/a	1800	3300	W	Awning

ID	Window type				U-value	SHGC
None Present						
Roof window	and skylight sch	edule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser

ID	Wall type		Insulation		Wa	II wrap or fo
EW-1	Brick Veneer	Bulk Insulation R1.5 No)		
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	3445	2790	SW	No	1950
Kitchen/Living	EW-1	1882	2790	S	No	2247
Kitchen/Living	EW-1	1956	2790	W	No	0
Kitchen/Living	EW-1	3824	2790	W	No	0

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	54.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	26.0	No insulation	No

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	13.2	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below	4.3	None	No Insulation	Ceramic Tiles

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616652-01 Certificate Date: 24 Feb 2020

★ Star rating:



Building features continued

	250mm				8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	35.4	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616629-01 Certificate Date: 24 Feb 2020 ★ Star rating: 7.1



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 705, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-001-03 A Aluminium A SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 69.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 74.0


Annual thermal performance loads (MJ/m²)

Heating: **35.8**Cooling: **28.2**TOTAL: **64.0**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

Unsealed: TOTAL:** **NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616629-01** Certificate Date:

24 Feb 2020

★ Star rating:



Building features

Window type	and performance value
Window ID	\M/:

Window ID	Window type	U-value	SHGC
ALM-001-03 A	ALM-001-03 A Aluminium A SG High Solar Gain Low-E	5.4	0.49

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-001-03 A	n/a	2700	2400	W	No Shading
Bedroom 1	ALM-001-03 A	n/a	1800	2000	W	Awning
Kitchen/Living	ALM-001-03 A	n/a	1800	3000	W	Awning
Kitchen/Living	ALM-001-03 A	n/a	2700	2700	N	No Shading

Roof windo	w and skylig	ht type and performanc	e value			
None Presen	Window t	type			U-value	SHGC
Roof windo	w and skylig	ht schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present	t					

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	3010	2790	W	No	3121
Bedroom 1	EW-1	3005	2790	W	No	0
Kitchen/Living	EW-1	4031	2790	W	No	0
Kitchen/Living	EW-1	3157	2790	N	No	4887

Internal wall type					
Wall type	Area (m²)	Insulation	Wall wrap or foil		
IW-1 - Shaft liner party wall with plaster	67.0	Bulk Insulation both sides of shaft liner R1.5	No		
IW-2 - Cavity wall, direct fix plasterboard, single gap	55.0	No insulation	No		

Floors						
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering	
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm	

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616629-01 Certificate Date: 24 Feb 2020



7.1

★ Star rating:

Building features continued Concrete Slab, Unit Below Bedroom 2 10.7 None No Insulation Carpet+Rubber Underlay 18mm 250mm Bath Concrete Slab, Unit Below 4.9 No Insulation **Ceramic Tiles** None 250mm 8mm Bedroom 1 Concrete Slab, Unit Below 15.3 None No Insulation Carpet+Rubber Underlay 18mm 250mm Concrete Slab, Unit Below Cork Tiles or Kitchen/Living 37.4 None No Insulation 250mm Parquetry 8mm

Ceiling type			
Location	Construction	Added insulation	Roof space above
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations					
Location	Number	Туре	Diameter (mm)	Sealed/unsealed	
Ens	1	Exhaust Fans	300	Sealed	
Bath	1	Exhaust Fans	300	Sealed	
Kitchen/Living	1	Exhaust Fans	300	Sealed	

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		-

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information						

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616595-02 Certificate Date: 24 Feb 2020 ★ Star rating: 6.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 706, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 73.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 78.0


Annual thermal performance loads (MJ/m²)

Heating: 26.7
Cooling: 51.8
TOTAL: 78.5

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616595-02** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window type	and performance value			
Window ID	Window type	U-value	SHGC	
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58	

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	2100	W	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	N	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	Awning
Bedroom 2	ALM-002-03 A	n/a	2700	2400	W	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	3600	W	No Shading

ID	Window	type			U-value	SHGC
None Presen	it					
Roof windo	w and skyligh	nt schedule				
Location	ID	Roof	Area (m²)	Orientation	Outdoor shade	Indoor

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	3081	2790	W	No	35
Bedroom 1	EW-1	5447	2790	N	No	35
Bedroom 1	EW-1	1092	2790	S	No	8596
Ens	EW-1	2220	2790	N	No	35
Bedroom 2	EW-1	3005	2790	W	No	2975
Bath	EW-1	917	2790	N	No	0
Bath	EW-1	743	2790	E	No	0
Bath	EW-1	618	2790	NE	No	0
Kitchen/Living	EW-1	1835	2790	S	No	4405
Kitchen/Living	EW-1	4102	2790	W	No	1134

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No
IW-2 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616595-02** Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	16.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bedroom 2	Concrete Slab, Unit Below 250mm	10.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	4.5	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	40.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling peneti	ations			
Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616553-01 Certificate Date: 24 Feb 2020 ★ Star rating: 6.9



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: **BERS Pro v4.4.0.0 (3.21)**

AAO: BDAV

Overview

Dwelling details

Street: Unit 707, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 74.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 79.0


Annual thermal performance loads (MJ/m²)

Heating: 21.6
Cooling: 44.5
TOTAL: 66.1

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:** 3

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Certificate number: **0004616553-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window type and	I performance value
-----------------	---------------------

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2400	E	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	2400	Е	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	3900	Е	No Shading

Roof window	w and skylight t	ype and performanc	e value			
ID None Present	Window typ	oe .			U-value	SHGC
Roof window	w and skylight s	chedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present						

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	3043	2790	E	No	3173
Bedroom 1	EW-1	1129	2790	S	No	11336
Bedroom 1	EW-1	2296	2790	N	No	0
Bedroom 1	EW-1	3250	2790	N	No	25
Bedroom 1	EW-1	2512	2790	E	No	71
Ens	EW-1	2257	2790	N	No	0
Bath	EW-1	1315	2790	NW	No	25
Bath	EW-1	846	2790	N	No	35
Kitchen/Living	EW-1	4111	2790	Е	No	1207
Kitchen/Living	EW-1	1980	2790	S	No	6947

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616553-01 Certificate Date: 24 Feb 2020

★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.5	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 1	Concrete Slab, Unit Below 250mm	15.8	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.6	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	41.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Ens	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Ceiling penetrations				
Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 708, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete, Plasterboard Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

No ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 73.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 78.0


Annual thermal performance loads (MJ/m²)

Heating: 18.9
Cooling: 39.9
TOTAL: 58.8

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Document Set ID: 9129545 Version: 1, Version Date: 08/05/2020

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616538-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	850	E	Awning
Bedroom 1	ALM-002-03 A	n/a	1800	1550	Е	Awning
Bedroom 2	ALM-002-03 A	n/a	2700	2400	E	No Shading
Kitchen/Living	ALM-002-03 A	n/a	1800	3000	Е	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	2700	N	No Shading

ID	Window t	уре		U-value	SHGC
None Present					
Roof window	w and skylight	schedule			
				Outdoor shade	

ID	Wall type		Insulation		Wall wrap or fo		
EW-1	Brick Veneer		Bulk Insulation R1.5		No		
External wall	schedule						
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 1	EW-1	950	2790	E	No	71	
Bedroom 1	EW-1	1773	2790	E	No	56	
Bedroom 1	EW-1	600	2790	NE	No	25	
Bedroom 2	EW-1	3073	2790	E	No	3042	
Kitchen/Living	EW-1	4172	2790	E	No	35	
Kitchen/Living	EW-1	3015	2790	N	No	5508	

Internal wall type					
Wall type	Area (m²)	Insulation	Wall wrap or foil		
IW-1 - Shaft liner party wall with plaster	71.0	Bulk Insulation both sides of shaft liner R1.5	No		
IW-2 - Cavity wall, direct fix plasterboard, single gap	57.0	No insulation	No		

Floors

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616538-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Ens	Concrete Slab, Unit Below 250mm	5.9	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	5.1	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	38.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Ens	Concrete, Plasterboard	No insulation	No
Bedroom 1	Concrete, Plasterboard	No insulation	No
Bedroom 2	Concrete, Plasterboard	No insulation	No
Bath	Concrete, Plasterboard	No insulation	No
Kitchen/Living	Concrete, Plasterboard	No insulation	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type		
Construction	Added insulation	Roof colour
None Present		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 801, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

R3.0 ceiling insulation No floor insulation

Glazing: ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 74.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 79.0


Annual thermal performance loads (MJ/m²)

Heating: 40.9
Cooling: 36.5
TOTAL: 77.4

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3

Unsealed: TOTAL:** **NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

0

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616504-01** Certificate Date: **24 Feb 2020**

★ Star rating:



Building features

Window type	Window type and performance value				
Window ID	Window type	U-value	SHGC		
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58		

Window schedule

Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
ALM-002-03 A	n/a	1800	900	NE	No Shading
ALM-002-03 A	n/a	1800	900	SE	Awning
ALM-002-03 A	n/a	2700	1800	NW	No Shading
ALM-002-03 A	n/a	1800	900	SE	Awning
ALM-002-03 A	n/a	2700	3600	NE	No Shading
ALM-002-03 A	n/a	1800	1500	NE	No Shading
ALM-002-03 A	n/a	1800	900	SE	Awning
	ALM-002-03 A ALM-002-03 A ALM-002-03 A ALM-002-03 A ALM-002-03 A ALM-002-03 A	ALM-002-03 A n/a	ALM-002-03 A n/a 1800 ALM-002-03 A n/a 1800 ALM-002-03 A n/a 2700 ALM-002-03 A n/a 1800 ALM-002-03 A n/a 2700 ALM-002-03 A n/a 2700 ALM-002-03 A n/a 1800	ALM-002-03 A n/a 1800 900 ALM-002-03 A n/a 1800 900 ALM-002-03 A n/a 2700 1800 ALM-002-03 A n/a 1800 900 ALM-002-03 A n/a 2700 3600 ALM-002-03 A n/a 1800 1500	ALM-002-03 A n/a 1800 900 NE ALM-002-03 A n/a 1800 900 SE ALM-002-03 A n/a 2700 1800 NW ALM-002-03 A n/a 1800 900 SE ALM-002-03 A n/a 2700 3600 NE ALM-002-03 A n/a 1800 1500 NE


ID	Window	type		U-value	SHGC
None Presen	t				
Roof windo	w and skyligh	nt schedule			

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	2800	2790	NE	No	0
Bedroom 1	EW-1	335	2790	Е	No	0
Bedroom 1	EW-1	320	2790	E	No	0
Bedroom 1	EW-1	3245	2790	SE	No	0
Bedroom 1	EW-1	1850	2790	NW	No	7050
Bedroom 2	EW-1	2795	2790	SE	No	0
Bedroom 2	EW-1	762	2790	SW	No	56
Bedroom 2	EW-1	610	2790	S	No	25
Kitchen/Living	EW-1	5945	2790	NE	No	1850
Kitchen/Living	EW-1	1900	2790	NW	No	1125
Ens	EW-1	2840	2790	SE	No	0

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
	59.0	No insulation	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616504-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features continued

IW-1 - Cavity wall, direct fix plasterboard, single gap

IW-2 - Shaft liner party wall with 41.0 Bulk Insulation both sides of shaft liner R1.5 No

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	5.0	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	13.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.7	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	43.1	None	No Insulation	Cork Tiles or Parquetry 8mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above
Bath	Plasterboard	Bulk Insulation R3	No
Bedroom 1	Plasterboard	Bulk Insulation R3	No
Bedroom 2	Plasterboard	Bulk Insulation R3	No
Kitchen/Living	Plasterboard	Bulk Insulation R3	No
Ens	Plasterboard	Bulk Insulation R3	No

rations			
Number	Туре	Diameter (mm)	Sealed/unsealed
1	Exhaust Fans	300	Sealed
1	Exhaust Fans	300	Sealed
1	Exhaust Fans	300	Sealed
		NumberType1Exhaust Fans1Exhaust Fans	Number Type Diameter (mm) 1 Exhaust Fans 300 1 Exhaust Fans 300

per Diameter (mm)
)

Roof type

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616504-01 Certificate Date: 24 Feb 2020 ★ Star rating:



: **6.4**

Building features continued

Construction	Added insulation	Roof colour
Concrete	No Insulation, Only an Air Gap	Light



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: **0004616470-01** Certificate Date: 24 Feb 2020 ★ Star rating: 5.9



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: 07 3069 5757

Declaration None

of interest:

BERS Pro v4.4.0.0 (3.21) Software:

BDAV AAO:

Overview

Dwelling details

Unit 802, Lot 3008 Lord Sheffield Circuit Street:

Suburb: Penrith

Postcode: State: **NSW** 2750 NCC Class: 2 **New Dwelling** Type:

NatHERS

climate zone: 28 Lot/DP

number: 3008/-Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

R3.0 ceiling insulation

No floor insulation

ALM-004-03 A Aluminium B DG Air Fill Glazing:

High Solar Gain low-E -Clear

Net floor area (m²)

Conditioned: 71.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 76.0


Annual thermal performance loads (MJ/m²)

Heating: 56.6 Cooling: 31.3 TOTAL: 88.0

Plan documents

11749, Revision E Plan ref/date:

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed:

Unsealed: 0 TOTAL:** 3

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616470-01 Certificate Date: 24 Feb 2020

2020 ★ Star rating:



Building features

Window type a	and performance value		
Window ID	Window type	U-value	SHGC
ALM-004-03 A	ALM-004-03 A Aluminium B DG Air Fill High Solar Gain low-E -Clear	4.3	0.53

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-004-03 A	n/a	2700	2700	SW	No Shading
Kitchen/Living	ALM-004-03 A	n/a	2700	3700	SW	No Shading
Bedroom 1	ALM-004-03 A	n/a	1800	900	SE	Awning
Bedroom 1	ALM-004-03 A	n/a	1800	2350	SW	Awning
Ens	ALM-004-03 A	n/a	1800	900	SE	Awning

ID	Window t	уре		U-value	SHGC
None Present					
Roof window	w and skylight	schedule			
				Outdoor shade	

ID	Wall type		Insulation		V	all wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	N	lo
EW-2	Brick Veneer		Foil, Anti-glare	e one side, Refle	ctive other	'es
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	2995	2790	SW	No	2925
Kitchen/Living	EW-1	3995	2790	SW	No	1175
Kitchen/Living	EW-1	1750	2790	NW	No	4725
Bedroom 1	EW-1	1150	2790	NW	No	8675
Bedroom 1	EW-1	4845	2790	SE	No	0
Bedroom 1	EW-1	707	2790	S	No	0
Bedroom 1	EW-1	2600	2790	SW	No	0
Ens	EW-1	2240	2790	SE	No	0
Bath	EW-1	1242	2790	E	No	0
Bath	EW-1	895	2790	SE	No	0

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Cavity wall, direct fix plasterboard, single gap	61.0	No insulation	No
IW-2 - Shaft liner party wall with	43.0	Bulk Insulation both sides of shaft liner R1.5	No

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616470-01** Certificate Date:

24 Feb 2020

★ Star rating:



Building features continued

plaster

Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.4	None	No Insulation	Carpet+Rubber Underlay 18mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	39.5	None	No Insulation	Cork Tiles or Parquetry 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.1	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.7	None	No Insulation	Ceramic Tiles 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 2	Plasterboard	Bulk Insulation R3	No
Kitchen/Living	Plasterboard	Bulk Insulation R3	No
Bedroom 1	Plasterboard	Bulk Insulation R3	No
Ens	Plasterboard	Bulk Insulation R3	No
Bath	Plasterboard	Bulk Insulation R3	No

Ceiling penetrations						
Location	Number	Туре	Diameter (mm)	Sealed/unsealed		
Kitchen/Living	1	Exhaust Fans	300	Sealed		
Ens	1	Exhaust Fans	300	Sealed		
Bath	1	Exhaust Fans	300	Sealed		

Location Number Diameter (mm)	
None Present	

Added insulation	Roof colour
	Light

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616470-01** Certificate Date:

24 Feb 2020 ★ S

★ Star rating:



Building features continued

No Insulation, Only an Air Gap

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616470-01 Certificate Date: 24 Feb 2020 ★ Star rating: 5.9



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616447-02 Certificate Date: 24 Feb 2020 ★ Star rating: 5.1



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: **BERS Pro v4.4.0.0 (3.21)**

AAO: BDAV

Overview

Dwelling details

Street: Unit 803, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

R3.0 ceiling insulation No floor insulation

Glazing: ALM-004-01 A Aluminium B DG Air Fill

Clear-Clear

Net floor area (m²)

Conditioned: 44.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 48.0


Annual thermal performance loads (MJ/m²)

Heating: **57.6**Cooling: **53.5**TOTAL: **111.1**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 2
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Page 1 of 4

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616447-02** Certificate Date:

24 Feb 2020 ★ Star rating:



Building features

Window	type and	performance value

Window ID	Window type	U-value	SHGC
ALM-004-01 A	ALM-004-01 A Aluminium B DG Air Fill Clear-Clear	4.8	0.59

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-004-01 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-004-01 A	n/a	1800	2100	SW	Awning
Kitchen/Living	ALM-004-01 A	n/a	1800	900	SW	Awning
Kitchen/Living	ALM-004-01 A	n/a	2700	2400	NW	No Shading

Roof window	w and skylight	type and performance	e value			
None Present	Window t	ype			U-value	SHGC
Roof window	w and skylight	schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present						

External wall	type						
ID	Wall type	Wall type Insulation			Wall wrap or foil		
EW-1	Brick Veneer	Bulk Insulation R1.5			No		
External wall schedule							
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 1	EW-1	2995	2790	SW	No	2600	
Kitchen/Living	EW-1	2850	2790	SE	No	3025	
Kitchen/Living	EW-1	3700	2790	SW	No	0	
Kitchen/Living	EW-1	2600	2790	NW	No	4450	

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	51.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	25.0	No insulation	No

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bath	Concrete Slab, Unit Below 250mm	4.2	None	No Insulation	Ceramic Tiles 8mm

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616447-02 Certificate Date: 24 Feb 2020

.020 ★ Star rating:



Building features continued						
Bedroom 1	Concrete Slab, Unit Below 250mm	12.1	None	No Insulation	Carpet+Rubber Underlay 18mm	
Kitchen/Living	Concrete Slab, Unit Below 250mm	31.7	None	No Insulation	Cork Tiles or Parquetry 8mm	

Ceiling type			
Location	Construction	Added insulation	Roof space above
Bath	Plasterboard	Bulk Insulation R3	No
Bedroom 1	Plasterboard	Bulk Insulation R3	No
Kitchen/Living	Plasterboard	Bulk Insulation R3	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type		
Construction	Added Finsulation	Roof colour
Concrete	No Insulation, Only an Air Gap	Light



Additional information		

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616413-01 Certificate Date: 24 Feb 2020 ★ Star rating: 5.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 804, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

R3.0 ceiling insulation No floor insulation

ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Glazing:

Conditioned: 49.0 Unconditioned: 4.0 Garage: 0.0 TOTAL: 53.0


Annual thermal performance loads (MJ/m²)

Heating: **57.7** Cooling: **41.7** TOTAL: **99.4**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 2

Unsealed: 0
TOTAL:***

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: **0004616413-01** Certificate Date: **24 Feb 2020**



★ Star rating:

Building features

Window type	and performand	e value				
Window ID	Window type				U-value	SHGC
ALM-002-03 A	ALM-002-03 A A	Aluminium B SG	High Solar Gain I	Low-E	5.4	0.58
Window sche	dule					
Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	2700	2400	SW	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	1200	W	Awning
Kitchen/Living	ALM-002-03 A	n/a	1800	3300	W	Awning

Root windo	w and skylight	type and performance	e value			
ID	Window ty	/ре			U-value	SHGC
None Presen	t					
Roof windo	w and skylight	schedule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Presen	†					

ID	Wall type		Insulation		Wa	II wrap or fo
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No)
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	3445	2790	SW	No	1950
Kitchen/Living	EW-1	1882	2790	S	No	2247
Kitchen/Living	EW-1	1956	2790	W	No	0
Kitchen/Living	EW-1	3824	2790	W	No	0

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	54.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	26.0	No insulation	No

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	13.2	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below	4.3	None	No Insulation	Ceramic Tiles

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616413-01** Certificate Date: **24 Feb 2020**

★ Star rating:



	8mm
Kitchen/Living Concrete Slab, Unit Below 35.4 None No Insu 250mm	lation Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 1	Plasterboard	Bulk Insulation R3	No
Bath	Plasterboard	Bulk Insulation R3	No
Kitchen/Living	Plasterboard	Bulk Insulation R3	No

Ceiling penetr	rations			
Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Location Number Diameter (mm)	
News Dissert	
None Present	

Roof type	
Construction	Added Roof colour insulation
Concrete	No Insulation, Light Only an Air Gap

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616389-01 Certificate Date: 24 Feb 2020 ★ Star rating: 6.1



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 805, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

R3.0 ceiling insulation No floor insulation

Glazing: ALM-001-03 A Aluminium A SG High

Solar Gain Low-E

Net floor area (m²)

Conditioned: 69.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 74.0


Annual thermal performance loads (MJ/m²)

Heating: **52.4** Cooling: **33.1** TOTAL: **85.5**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3
Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

3

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616389-01 Certificate Date: 24 Fe

24 Feb 2020 ★ Star rating:



Building features

Window type and per	formance value
---------------------	----------------

Window ID	Window type	U-value	SHGC
ALM-001-03 A	ALM-001-03 A Aluminium A SG High Solar Gain Low-E	5.4	0.49

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-001-03 A	n/a	2700	2400	W	No Shading
Bedroom 1	ALM-001-03 A	n/a	1800	2000	W	Awning
Kitchen/Living	ALM-001-03 A	n/a	1800	3000	W	Awning
Kitchen/Living	ALM-001-03 A	n/a	2700	2700	N	No Shading

Roof window	and skylight type	e and performanc	e value			
None Present	Window type				U-value	SHGC
Roof window	and skylight sch	edule				
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser
None Present			-			

ID	Wall type		Insulation		Wa	II wrap or foi
EW-1	Brick Veneer		Bulk Insulation	n R1.5	No	<u> </u>
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 2	EW-1	3010	2790	W	No	3121
Bedroom 1	EW-1	3005	2790	W	No	0
Kitchen/Living	EW-1	4031	2790	W	No	0
Kitchen/Living	EW-1	3157	2790	N	No	4887

Internal wall type			
Wall type	Area (m²)	Insulation	Wall wrap or foil
IW-1 - Shaft liner party wall with plaster	67.0	Bulk Insulation both sides of shaft liner R1.5	No
IW-2 - Cavity wall, direct fix plasterboard, single gap	55.0	No insulation	No

Floors					
Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616389-01 Certificate Date: 24 Feb 2020

★ Star rating:

NATIONWIDE HOUSE ENERGY PATING SCHEM

Building features continued Bedroom 2 10.7 Concrete Slab, Unit Below None No Insulation Carpet+Rubber Underlay 18mm 250mm Bath Concrete Slab, Unit Below 4.9 No Insulation **Ceramic Tiles** None 250mm 8mm Bedroom 1 Concrete Slab, Unit Below 15.3 None No Insulation Carpet+Rubber Underlay 18mm 250mm Concrete Slab, Unit Below Cork Tiles or Kitchen/Living 37.4 None No Insulation 250mm Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Ens	Plasterboard	Bulk Insulation R3	No
Bedroom 2	Plasterboard	Bulk Insulation R3	No
Bath	Plasterboard	Bulk Insulation R3	No
Bedroom 1	Plasterboard	Bulk Insulation R3	No
Kitchen/Living	Plasterboard	Bulk Insulation R3	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type	
Construction	Added Roof colour insulation
Concrete	No Insulation, Light Only an Air Gap

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate number: 0004616355-01 Certificate Date: 24 Feb 2020 ★ Star rating: 5.4



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 806, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

R3.0 ceiling insulation No floor insulation

ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Glazing:

Conditioned: 73.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 78.0


Annual thermal performance loads (MJ/m²)

Heating: 43.0 Cooling: 57.9 TOTAL: 100.9

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3 Unsealed: 0

TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616355-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Building features

Window ID	Window type	Hyalua	SHGC
Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 1	ALM-002-03 A	n/a	1800	2100	W	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	900	N	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	Awning
Bedroom 2	ALM-002-03 A	n/a	2700	2400	W	No Shading
Kitchen/Living	ALM-002-03 A	n/a	2700	3600	W	No Shading

ID	Window	type			U-value	SHGC
None Presen	it					
Roof windo	w and skyligh	nt schedule				
Location	ID	Roof	Area (m²)	Orientation	Outdoor shade	Indoor

ID	Wall type		Insulation	Insulation Wa		
EW-1	Brick Veneer	Bulk Insulation R1.5		No		
External wall	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	3081	2790	W	No	35
Bedroom 1	EW-1	5447	2790	N	No	35
Bedroom 1	EW-1	1092	2790	S	No	8596
Ens	EW-1	2220	2790	N	No	35
Bedroom 2	EW-1	3005	2790	W	No	2975
Bath	EW-1	917	2790	N	No	0
Bath	EW-1	743	2790	E	No	0
Bath	EW-1	618	2790	NE	No	0
Kitchen/Living	EW-1	1835	2790	S	No	4405
Kitchen/Living	EW-1	4102	2790	W	No	1134

Internal wall type					
Wall type	Area (m²)	Insulation	Wall wrap or foil		
IW-1 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No		
IW-2 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: 0004616355-01 Certificate Date: 24 Feb 2020 ★ Star rating:



Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 1	Concrete Slab, Unit Below 250mm	16.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.5	None	No Insulation	Ceramic Tiles 8mm
Bedroom 2	Concrete Slab, Unit Below 250mm	10.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	4.5	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	40.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 1	Plasterboard	Bulk Insulation R3	No
Ens	Plasterboard	Bulk Insulation R3	No
Bedroom 2	Plasterboard	Bulk Insulation R3	No
Bath	Plasterboard	Bulk Insulation R3	No
Kitchen/Living	Plasterboard	Bulk Insulation R3	No

Ceiling penetrations					
Location	Number	Туре	Diameter (mm)	Sealed/unsealed	
Ens	1	Exhaust Fans	300	Sealed	
Bath	1	Exhaust Fans	300	Sealed	
Kitchen/Living	1	Exhaust Fans	300	Sealed	

Ceiling fans		
Location	Number	Diameter (mm)
None Present		

Roof type	
Construction	Added Roof colour insulation
Concrete	No Insulation, Light Only an Air Gap

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact



Assessor details

Accreditation

number: VIC/BDAV/16/1757
Name: Conor Horwood

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: **07 3069 5757**

Declaration None

of interest:

Software: BERS Pro v4.4.0.0 (3.21)

AAO: BDAV

Overview

Dwelling details

Street: Unit 807, Lot 3008 Lord Sheffield Circuit

Suburb: Penrith

State: NSW Postcode: 2750
Type: New Dwelling NCC Class: 2

NatHERS

Lot/DP climate zone: 28

number: 3008/- Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

R3.0 ceiling insulation No floor insulation

ALM-002-03 A Aluminium B SG High

Solar Gain Low-E

Net floor area (m²)

Glazing:

Conditioned: 74.0
Unconditioned: 5.0
Garage: 0.0
TOTAL: 79.0


Annual thermal performance loads (MJ/m²)

Heating: **35.3**Cooling: **49.8**TOTAL: **85.2**

Plan documents

Plan ref/date: 11749, Revision E

Prepared by: **DKO**



Ceiling penetrations

(see following pages for details)

Sealed: 3 Unsealed: 0

Unsealed: 0
TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

Window selection - default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616322-01 Certificate Date: 2

24 Feb 2020 ★ Star rating:



Building features

Window ID	Window type	U-value	SHGC
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58

Window schedule

Location	Window ID	Window no.	Height (mm)	Width (mm)	Orientation	Outdoor shade
Bedroom 2	ALM-002-03 A	n/a	2700	2400	E	No Shading
Bedroom 1	ALM-002-03 A	n/a	1800	2400	E	No Shading
Ens	ALM-002-03 A	n/a	1800	900	N	Awning
Kitchen/Living	ALM-002-03 A	n/a	2700	3900	Е	No Shading

Roof window and skylight type and performance value								
None Present	Window ty	ре			U-value	SHGC		
Roof window and skylight schedule								
Location	ID	Roof window/skylight no.	Area (m²)	Orientation	Outdoor shade	Indoor shade/diffuser		
None Present								

ID	Wall type		Insulation		Wa	Wall wrap or foil	
EW-1	Brick Veneer	Bulk Insulation R1.5		No			
External wall schedule							
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)	
Bedroom 2	EW-1	3043	2790	E	No	3173	
Bedroom 1	EW-1	1129	2790	S	No	11336	
Bedroom 1	EW-1	2296	2790	N	No	0	
Bedroom 1	EW-1	3250	2790	N	No	25	
Bedroom 1	EW-1	2512	2790	Е	No	71	
Ens	EW-1	2257	2790	N	No	0	
Bath	EW-1	1315	2790	NW	No	25	
Bath	EW-1	846	2790	N	No	35	
Kitchen/Living	EW-1	4111	2790	Е	No	1207	
Kitchen/Living	EW-1	1980	2790	S	No	6947	

Internal wall type						
Wall type	Area (m²)	Insulation	Wall wrap or foil			
IW-1 - Shaft liner party wall with plaster	44.0	Bulk Insulation both sides of shaft liner R1.5	No			
IW-2 - Cavity wall, direct fix plasterboard, single gap	62.0	No insulation	No			

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616322-01** Certificate Date:

24 Feb 2020

★ Star rating:



Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Bedroom 2	Concrete Slab, Unit Below 250mm	10.5	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 1	Concrete Slab, Unit Below 250mm	15.8	None	No Insulation	Carpet+Rubber Underlay 18mm
Ens	Concrete Slab, Unit Below 250mm	5.7	None	No Insulation	Ceramic Tiles 8mm
Bath	Concrete Slab, Unit Below 250mm	4.6	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	41.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Location	Construction	Added insulation	Roof space above
Bedroom 2	Plasterboard	Bulk Insulation R3	No
Bedroom 1	Plasterboard	Bulk Insulation R3	No
Ens	Plasterboard	Bulk Insulation R3	No
Bath	Plasterboard	Bulk Insulation R3	No
Kitchen/Living	Plasterboard	Bulk Insulation R3	No

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type			
Construction	Added Roof colour insulation		
Concrete	No Insulation, Light Only an Air Gap		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact

Certificate Date: 24 Feb 2020 Certificate number: **0004616280-02** ★ Star rating: 6.4



Assessor details

Accreditation

VIC/BDAV/16/1757 number: Name: **Conor Horwood**

Organisation: Accelerate Sustainability Assessments

Email: conor.horwood@accsa.net.au

Phone: 07 3069 5757

Declaration None

of interest:

BERS Pro v4.4.0.0 (3.21) Software:

BDAV AAO:

Overview

Dwelling details

Unit 808, Lot 3008 Lord Sheffield Circuit Street:

Suburb: Penrith

Postcode: State: **NSW** 2750 NCC Class: 2 **New Dwelling** Type:

NatHERS

climate zone: 28 Lot/DP

number: 3008/-Exposure: Open

Key construction and insulation materials

(see following pages for details)

Construction: Brick Veneer

Concrete

Concrete Slab, Unit Below

Insulation: R1.5 wall insulation

R3.0 ceiling insulation

No floor insulation

ALM-002-03 A Aluminium B SG High Glazing:

Solar Gain Low-E

Net floor area (m²)

Conditioned: 73.0 Unconditioned: 5.0 Garage: 0.0 TOTAL: 78.0

Annual thermal performance loads (MJ/m²)

Heating: 32.7 Cooling: 45.3 TOTAL: 78.0

Plan documents

11749, Revision E Plan ref/date:

Prepared by: **DKO**

the more energy efficient NATIONWIDE Predicted annual energy load for heating and cooling based on standard occupancy assumptions MJ/m² For more information on your dwelling's rating see: www.nathers.gov.au

Ceiling penetrations

(see following pages for details)

Sealed: 3

Unsealed: TOTAL:**

**NOTE: This total is the maximum number of ceiling penetrations allowed to a ceiling (under a roof) for this certificate. If this number is exceded in construction then this certificate IS NOT VALID and a new certificate is required. Loss of ceiling insulation for the penetrations listed has been taken into account with the rating.

Principle downlight type: Unknown

0

3

Window selection default windows only

Note on allowable window values: Only a 5% tolerance to the nominated SHGC window values shown on page 2 can be used with this rating.

Note: Only a +/- 5% SHGC tolerance is allowed with this rating.

NB: This tolerance ONLY applies to SHGC, the U-value can always be lower but not higher than the values stated on page 2.

If any of windows selected are outside the 5% tolerance then this certificate is no longer valid and the dwelling will need to be rerated to confirm compliance.

Scan to access this certificate online and confirm this is valid.



Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au Document Set ID: 9129545

Certificate number: 0004616280-02 Certificate Date: 24 Feb 2020

★ Star rating:



Building features

Window type and performance value					
Window ID	Window type	U-value	SHGC		
ALM-002-03 A	ALM-002-03 A Aluminium B SG High Solar Gain Low-E	5.4	0.58		

Window schedule

Bedroom 1 ALM-002-03 A Bedroom 1 ALM-002-03 A	n/a	1800	850	E	Awning
Redroom 1 ΔI M-002-03 Δ					•
Dedition 1 ALW 002 00 A	n/a	1800	1550	Е	Awning
Bedroom 2 ALM-002-03 A	n/a	2700	2400	Е	No Shading
Kitchen/Living ALM-002-03 A	n/a	1800	3000	E	No Shading
Kitchen/Living ALM-002-03 A	n/a	2700	2700	N	No Shading

ID	Window t	уре		U-value	SHGC
None Present					
Roof window	w and skylight	schedule			
		Roof	Area (m ²)	 Outdoor shade	

ID	Wall type		Insulation		Wa	II wrap or fo
EW-1	Brick Veneer		Bulk Insulation R1.5		No	
External wall s	schedule					
Location	ID	Width (mm)	Height (mm)	Orientation	Fixed Shade	Eaves (mm)
Bedroom 1	EW-1	950	2790	E	No	71
Bedroom 1	EW-1	1773	2790	E	No	56
Bedroom 1	EW-1	600	2790	NE	No	25
Bedroom 2	EW-1	3073	2790	E	No	3042
Kitchen/Living	EW-1	4172	2790	E	No	35
Kitchen/Living	EW-1	3015	2790	N	No	5508

Internal wall type				
Wall type	Area (m²)	Insulation	Wall wrap or foil	
IW-1 - Shaft liner party wall with plaster	71.0	Bulk Insulation both sides of shaft liner R1.5	No	
IW-2 - Cavity wall, direct fix plasterboard, single gap	57.0	No insulation	No	

Floors

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au

Certificate number: **0004616280-02** Certificate Date: **24 Feb 2020**

★ Star rating:



Location	Construction	Area (m²)	Sub floor ventilation	Added insulation	Covering
Ens	Concrete Slab, Unit Below 250mm	5.9	None	No Insulation	Ceramic Tiles 8mm
Bedroom 1	Concrete Slab, Unit Below 250mm	16.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bedroom 2	Concrete Slab, Unit Below 250mm	11.6	None	No Insulation	Carpet+Rubber Underlay 18mm
Bath	Concrete Slab, Unit Below 250mm	5.1	None	No Insulation	Ceramic Tiles 8mm
Kitchen/Living	Concrete Slab, Unit Below 250mm	38.9	None	No Insulation	Cork Tiles or Parquetry 8mm

Ceiling type				
Location	Construction	Added insulation	Roof space above	
Ens	Plasterboard	Bulk Insulation R3	No	
Bedroom 1	Plasterboard	Bulk Insulation R3	No	
Bedroom 2	Plasterboard	Bulk Insulation R3	No	
Bath	Plasterboard	Bulk Insulation R3	No	
Kitchen/Living	Plasterboard	Bulk Insulation R3	No	

Location	Number	Туре	Diameter (mm)	Sealed/unsealed
Ens	1	Exhaust Fans	300	Sealed
Bath	1	Exhaust Fans	300	Sealed
Kitchen/Living	1	Exhaust Fans	300	Sealed

Ceiling fans			
Location	Number	Diameter (mm)	
None Present			

Roof type			
Construction	Added Roof colour insulation		
Concrete	No Insulation, Light Only an Air Gap		

^{*} Nationwide House Energy Rating Scheme (NatHERS) is an initiative of the Australian, state and territory governments. For more details see www.nathers.gov.au



Additional information	

Explanatory notes

About this report

Residential energy ratings address the quality of the building fabric i.e. walls, windows, floors and roof/ceilings. Ratings do not cover the energy or water efficiency of appliances including heating and cooling, hot water, dishwashers, ovens, fridges, TVs etc. or solar panel or water tank requirements. The efficiency or specification of these items is generally covered by other regulations, standards or guidelines.

General Information

A NatHERS House Energy Rating is a comprehensive, dynamic computer modelling evaluation of the floorplans, elevations and specifications to predict an energy load of a home. Not all of us use our homes in the same way, so ratings are generated using standard assumptions. This means homes can be compared across the country.

The actual energy consumption of your home may vary significantly from the predicted energy load figures in the report depending on issues such as the size of your household and your personal preferences, e.g. in terms of heating or cooling.

While the figures are an indicative guide to energy use, they can be used as a reliable guide for comparative purposes between different house designs and for demonstrating that the design meets the required regulatory compliance.

Homes that are energy efficient use less energy, are warmer in winter, cooler in summer and cost less to run. The higher the star rating the more energy efficient.

This NatHERS House Energy Rating report was carefully prepared by your assessor on the basis of comprehensive modelling using standard procedures to rate your home using the underlying engine developed by the Australian Commonwealth Scientific and Industrial Research Organisation (CSIRO).

All information relating to energy loads presented in this report is based on a range of standard assumptions in order to allow for comparisons with reports prepared for other homes and to demonstrate minimum regulatory compliance.

The standard assumptions include figures for occupancy, indoor air temperature and are based on a unique climate file for your region.

Accredited Assessors

To ensure you get a high-quality, professional NatHERS House Energy Rating report, you should always use an accredited assessor, accredited assessors are members of a professional body called an Assessor Accrediting Organisation (AAO).

AAOs have specific quality assurance processes in place and continuing professional development requirements to maintain a high and consistent standard of assessments across the country. Non-accredited assessors do not have this level of quality assurance or any on-going training requirements.

If you have any questions or concerns about this report, please direct them to your assessor in the first instance.

If your assessor is unable to address your questions or concerns, please contact their AAO listed under 'assessor details'. You can also find a range of information about accredited assessors on the AAO websites.

Disclaimer

The energy values quoted are for comparison purposes only; they are not a prediction of actual energy use. This rating only applies to the floor plan, construction details, orientation and climate as submitted and included in the attached drawing set that bears a stamp with the same number as this certificate. Changes to any of these details could affect the rating.

Contact